


# **OIL ANALYSIS REPORT**

### Sample Rating Trend



# NORMAL



Machine Id
221091
Component
Diesel Engine

PETRO CANADA DURON SHP 15W40 (--- LTR)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.


## **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


LIK)		Jun2021	Oct2021 Mar2022	Dec2022 Jun2023 Ja	n2024		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0092592	GFL0092584	GFL0092553	
Sample Date		Client Info		24 Apr 2024	03 Jan 2024	19 Sep 2023	
Machine Age	hrs	Client Info		9959	9191	8701	
Oil Age	hrs	Client Info		600	600	600	
Oil Changed		Client Info		Changed	Oil Added	Changed	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	NEG	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>80	4	6	12	
Chromium	ppm	ASTM D5185m	>5	<1	<1	<1	
Nickel	ppm	ASTM D5185m	>2	0	0	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m	>3	0	0	0	
Aluminum	ppm	ASTM D5185m	>30	1	2	<1	
Lead	ppm	ASTM D5185m	>30	0	0	2	
Copper	ppm	ASTM D5185m	>150	0	<1	1	
Tin	ppm	ASTM D5185m	>5	<1	<1	<1	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	2	5	3	
Barium	ppm	ASTM D5185m	0	0	0	0	
Molybdenum	ppm	ASTM D5185m	60	55	58	64	
Manganese	ppm	ASTM D5185m	0	0	<1	<1	
Magnesium	ppm	ASTM D5185m	1010	876	891	967	
Calcium	ppm	ASTM D5185m	1070	995	1050	1201	
Phosphorus	ppm	ASTM D5185m	1150	1023	1022	1082	
Zinc	ppm	ASTM D5185m	1270	1186	1233	1327	
Sulfur	ppm	ASTM D5185m	2060	3369	3100	3751	
CONTAMINAN	ITS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>20	2	2	4	
Sodium	ppm	ASTM D5185m		2	2	5	
Potassium	ppm	ASTM D5185m	>20	<1	3	8	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.4	0.3	0.5	
Nitration	Abs/cm	*ASTM D7624	>20	6.3	5.3	9.1	
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.6	18.1	21.0	
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.5	13.6	16.6	
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.8	9.0	8.0	



## **OIL ANALYSIS REPORT**










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	RHES	metnoa	ilmit/base	current	nistory i	nistory2
Visc @ 100°C	cSt	ASTM D445	15.4	13.3	14.3	13.8

## **GRAPHS**













Certificate 12367

Laboratory Sample No.

: GFL0092592 Lab Number : 06160156 Unique Number : 10995579

Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 25 Apr 2024 **Tested** : 26 Apr 2024

Diagnosed : 26 Apr 2024 - Wes Davis

GFL Environmental - 885 - Orlando

1263 W Landstreet Rd Orlando, FL US 32824

Contact: DAWN WALLACE

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: