

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
MACK 2419
Component
Diesel Engine
Fluid
CERTIFIED SPECTRA XTREME 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a components first oil change.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0107634	---	---
Sample Date	Client Info		17 Apr 2024	---	---
Machine Age	mls	Client Info	19640	---	---
Oil Age	mls	Client Info	19640	---	---
Oil Changed	Client Info		Changed	---	---
Sample Status			NORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	---	---
Water	WC Method	>0.2	NEG	---	---
Glycol	WC Method		NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>120	41	---
Chromium	ppm	ASTM D5185m	>20	1	---
Nickel	ppm	ASTM D5185m	>5	2	---
Titanium	ppm	ASTM D5185m	>2	<1	---
Silver	ppm	ASTM D5185m	>2	<1	---
Aluminum	ppm	ASTM D5185m	>20	29	---
Lead	ppm	ASTM D5185m	>40	0	---
Copper	ppm	ASTM D5185m	>330	59	---
Tin	ppm	ASTM D5185m	>15	4	---
Vanadium	ppm	ASTM D5185m		0	---
Cadmium	ppm	ASTM D5185m		0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		116	---
Barium	ppm	ASTM D5185m		<1	---
Molybdenum	ppm	ASTM D5185m		138	---
Manganese	ppm	ASTM D5185m		6	---
Magnesium	ppm	ASTM D5185m		764	---
Calcium	ppm	ASTM D5185m		1532	---
Phosphorus	ppm	ASTM D5185m		728	---
Zinc	ppm	ASTM D5185m		829	---
Sulfur	ppm	ASTM D5185m		2507	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	64	---
Sodium	ppm	ASTM D5185m		3	---
Potassium	ppm	ASTM D5185m	>20	69	---




INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>4	0.5	---
Nitration	Abs/cm	*ASTM D7624	>20	10.8	---
Sulfation	Abs./1mm	*ASTM D7415	>30	24.3	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs./1mm	*ASTM D7414	>25	23.3	---
Base Number (BN)	mg KOH/g	ASTM D2896		6.5	---





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	9.6	---	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0107634
Lab Number : **06160175**
Unique Number : 10995598
Test Package : FLEET

Received : 25 Apr 2024
Tested : 26 Apr 2024
Diagnosed : 26 Apr 2024 - Wes Davis

Z FORCE TRANSPORTATION INC
 700 E JOE ORR RD
 CHICAGO HEIGHTS, IL
 US 60411
 Contact: MIKE PROCANIN
 mprocanin@zforcetransportation.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: