




# OIL ANALYSIS REPORT



Area  
**(QB18889)**  
 Machine Id  
**913022**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

Sample Rating Trend



**NORMAL**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1    | history2    |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info |             | <b>GFL0116137</b>  | GFL0104557  | GFL0092615  |
| Sample Date   | Client Info |             | <b>22 Apr 2024</b> | 05 Feb 2024 | 06 Nov 2023 |
| Machine Age   | hrs         | Client Info | <b>3603</b>        | 3032        | 2423        |
| Oil Age       | hrs         | Client Info | <b>571</b>         | 610         | 605         |
| Oil Changed   | Client Info |             | <b>Changed</b>     | Changed     | Not Changed |
| Sample Status |             |             | <b>NORMAL</b>      | NORMAL      | NORMAL      |

## CONTAMINATION

|        | method    | limit/base | current        | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel   | WC Method | >3.0       | <b>&lt;1.0</b> | <1.0     | <1.0     |
| Water  | WC Method | >0.2       | <b>NEG</b>     | NEG      | NEG      |
| Glycol | WC Method |            | <b>NEG</b>     | NEG      | NEG      |

## WEAR METALS

|          | method | limit/base       | current      | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron     | ppm    | ASTM D5185m >120 | <b>14</b>    | 14       | 18       |
| Chromium | ppm    | ASTM D5185m >20  | <b>1</b>     | <1       | <1       |
| Nickel   | ppm    | ASTM D5185m >5   | <b>3</b>     | 3        | 2        |
| Titanium | ppm    | ASTM D5185m >2   | <b>&lt;1</b> | 0        | <1       |
| Silver   | ppm    | ASTM D5185m >2   | <b>0</b>     | <1       | 0        |
| Aluminum | ppm    | ASTM D5185m >20  | <b>3</b>     | 2        | 1        |
| Lead     | ppm    | ASTM D5185m >40  | <b>1</b>     | <1       | <1       |
| Copper   | ppm    | ASTM D5185m >330 | <b>6</b>     | 14       | 30       |
| Tin      | ppm    | ASTM D5185m >15  | <b>1</b>     | 1        | 1        |
| Vanadium | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |
| Cadmium  | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |

## ADDITIVES

|            | method | limit/base       | current      | history1 | history2 |
|------------|--------|------------------|--------------|----------|----------|
| Boron      | ppm    | ASTM D5185m 0    | <b>&lt;1</b> | 3        | 0        |
| Barium     | ppm    | ASTM D5185m 0    | <b>0</b>     | 0        | 0        |
| Molybdenum | ppm    | ASTM D5185m 60   | <b>61</b>    | 61       | 60       |
| Manganese  | ppm    | ASTM D5185m 0    | <b>1</b>     | <1       | <1       |
| Magnesium  | ppm    | ASTM D5185m 1010 | <b>1025</b>  | 997      | 951      |
| Calcium    | ppm    | ASTM D5185m 1070 | <b>1096</b>  | 1071     | 1059     |
| Phosphorus | ppm    | ASTM D5185m 1150 | <b>1175</b>  | 1072     | 947      |
| Zinc       | ppm    | ASTM D5185m 1270 | <b>1313</b>  | 1335     | 1273     |
| Sulfur     | ppm    | ASTM D5185m 2060 | <b>3491</b>  | 2798     | 2398     |

## CONTAMINANTS

|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >25 | <b>5</b> | 4        | 5        |
| Sodium    | ppm    | ASTM D5185m     | <b>5</b> | 4        | 4        |
| Potassium | ppm    | ASTM D5185m >20 | <b>2</b> | 1        | 3        |

## INFRA-RED




|           | method   | limit/base      | current     | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot %    | %        | *ASTM D7844 >4  | <b>0.8</b>  | 0.7      | 0.8      |
| Nitration | Abs/cm   | *ASTM D7624 >20 | <b>8.7</b>  | 9.2      | 9.3      |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | <b>20.4</b> | 20.8     | 21.5     |

## FLUID DEGRADATION

|                  | method   | limit/base      | current     | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm | *ASTM D7414 >25 | <b>16.7</b> | 17.6     | 18.1     |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8  | <b>7.3</b>  | 6.9      | 7.1      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Yellow Metal     | scalar | *Visual    | NONE    | NONE     | NONE     |
| Precipitate      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Silt             | scalar | *Visual    | NONE    | NONE     | NONE     |
| Debris           | scalar | *Visual    | NONE    | NONE     | NONE     |
| Sand/Dirt        | scalar | *Visual    | NONE    | NONE     | NONE     |
| Appearance       | scalar | *Visual    | NORML   | NORML    | NORML    |
| Odor             | scalar | *Visual    | NORML   | NORML    | NORML    |
| Emulsified Water | scalar | *Visual    | >0.2    | NEG      | NEG      |
| Free Water       | scalar | *Visual    |         | NEG      | NEG      |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 100°C     | cSt    | ASTM D445  | 15.4    | 14.2     | 13.9     |

## GRAPHS



Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0116137  
**Lab Number** : 06161074  
**Unique Number** : 10996497  
**Test Package** : FLEET  
**Received** : 25 Apr 2024  
**Tested** : 26 Apr 2024  
**Diagnosed** : 26 Apr 2024 - Wes Davis

**GFL Environmental - 947 - WB Horicon HC**  
 N7296 County Rd V  
 Horicon, WI  
 US 53032  
 Contact: Tim Kieffer  
 tim.kieffer@gflenv.com  
 T: (608)219-0288  
 F: