


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id
849
 Component
Front Differential
 Fluid
GEAR OIL SAE 75W90 (--- GAL)

DIAGNOSIS

Recommendation
 We advise that you check all areas where dirt can enter the system. Resample at the next service interval to monitor.

Wear
 All component wear rates are normal.

Contamination
 Moderate concentration of visible dirt/debris present in the oil. Elemental level of silicon (Si) above normal.

Fluid Condition
 The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0119935	PCA0107455	---
Sample Date	Client Info		02 May 2024	05 Dec 2023	---
Machine Age	mls	Client Info	101623	0	---
Oil Age	mls	Client Info	0	0	---
Oil Changed	Client Info		Not Chngd	N/A	---
Sample Status			ABNORMAL	ABNORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>.2	NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >500	155	183	---
Chromium	ppm	ASTM D5185m >10	1	2	---
Nickel	ppm	ASTM D5185m >10	3	5	---
Titanium	ppm	ASTM D5185m	<1	<1	---
Silver	ppm	ASTM D5185m	0	0	---
Aluminum	ppm	ASTM D5185m >25	3	3	---
Lead	ppm	ASTM D5185m >25	0	0	---
Copper	ppm	ASTM D5185m >100	1	2	---
Tin	ppm	ASTM D5185m >10	0	0	---
Vanadium	ppm	ASTM D5185m	<1	0	---
Cadmium	ppm	ASTM D5185m	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 400	262	152	---
Barium	ppm	ASTM D5185m 200	<1	0	---
Molybdenum	ppm	ASTM D5185m 12	7	0	---
Manganese	ppm	ASTM D5185m	2	3	---
Magnesium	ppm	ASTM D5185m 12	32	5	---
Calcium	ppm	ASTM D5185m 150	152	23	---
Phosphorus	ppm	ASTM D5185m 1650	1336	1056	---
Zinc	ppm	ASTM D5185m 125	109	<1	---
Sulfur	ppm	ASTM D5185m 22500	25379	24542	---



CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >75	▲ 98	▲ 175	---
Sodium	ppm	ASTM D5185m	<1	3	---
Potassium	ppm	ASTM D5185m >20	2	3	---

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual NONE	NONE	NONE	---
Precipitate	scalar	*Visual NONE	NONE	NONE	---
Silt	scalar	*Visual NONE	NONE	NONE	---
Debris	scalar	*Visual NONE	▲ MODER	NONE	---
Sand/Dirt	scalar	*Visual NONE	NONE	NONE	---
Appearance	scalar	*Visual NORML	NORML	NORML	---
Odor	scalar	*Visual NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual >.2	NEG	NEG	---
Free Water	scalar	*Visual	NEG	NEG	---

OIL ANALYSIS REPORT






FLUID PROPERTIES

method	limit/base	current	history1	history2
Visc @ 40°C	cSt ASTM D445	109	85.9	94.2

SAMPLE IMAGES

method	limit/base	current	history1	history2
Color			no image	no image
Bottom			no image	no image

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0119935 **Received** : 09 May 2024
Lab Number : **06174397** **Tested** : 10 May 2024
Unique Number : 11020450 **Diagnosed** : 13 May 2024 - Don Baldrige
Test Package : FLEET

NW WHITE & CO - COLUMBIA DIVISION
 100 INDEPENDENCE BLVD
 COLUMBIA, SC
 US 29210
 Contact: GEORGE EDWARDS
 gedwards@nwwhite.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)