




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

724002

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (26 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0115832	GFL0111008	GFL0110994
Sample Date	Client Info		01 May 2024	14 Feb 2024	22 Jan 2024
Machine Age	hrs	Client Info	22545	22508	22495
Oil Age	hrs	Client Info	490	0	0
Oil Changed	Client Info		Not Chngd	N/A	N/A
Sample Status			NORMAL	ABNORMAL	ABNORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >75	4	▲ 167	▲ 159
Chromium	ppm	ASTM D5185m >5	0	5	3
Nickel	ppm	ASTM D5185m >4	0	3	3
Titanium	ppm	ASTM D5185m >2	0	<1	0
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >15	1	10	8
Lead	ppm	ASTM D5185m >25	2	0	0
Copper	ppm	ASTM D5185m >100	0	2	<1
Tin	ppm	ASTM D5185m >4	<1	0	0
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	11	6	5
Barium	ppm	ASTM D5185m 0	0	0	<1
Molybdenum	ppm	ASTM D5185m 60	65	63	61
Manganese	ppm	ASTM D5185m 0	<1	1	1
Magnesium	ppm	ASTM D5185m 1010	908	945	858
Calcium	ppm	ASTM D5185m 1070	1033	1127	980
Phosphorus	ppm	ASTM D5185m 1150	1040	1045	974
Zinc	ppm	ASTM D5185m 1270	1187	1217	1160
Sulfur	ppm	ASTM D5185m 2060	3496	3068	2692

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	4	14	11
Sodium	ppm	ASTM D5185m	12	5	<1
Potassium	ppm	ASTM D5185m >20	2	3	1

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	0.1	1.4	0.5
Nitration	Abs/cm	*ASTM D7624 >20	5.1	7.3	5.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	17.2	20.3	18.3


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	13.0	13.8	13.4
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	9.6	9.7	9.0




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C



VISUAL


	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES


	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	12.8	14.7

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0115832
Lab Number : 06175183
Unique Number : 11021236
Test Package : FLEET

Received : 10 May 2024
Tested : 11 May 2024
Diagnosed : 11 May 2024 - Wes Davis

GFL Environmental - 868 - Childersburg Fines Hauling (Alpine)
 13737 Plant Rd
 Childersburg, AL
 US 35044

Contact: JONATHAN WILLIAMS
 jonathan.williams@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: