


OIL ANALYSIS REPORT



Machine Id **CELL 1 GRINDER 1**

Component **Gearbox**

MOBIL SHC CIBUS 220 (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Αρ <u>υ</u> 2021 Μση2023 Μση2024				
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0118366	PCA0092044	PCA0044835
Sample Date		Client Info		07 May 2024	02 May 2023	26 Apr 2021
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ATTENTION	ABNORMAL	ABNORMAL
CONTAMINATION	NC	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS	}	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	3	22	18
Chromium	ppm	ASTM D5185m	>15	<1	0	<1
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	<1	0
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	<1	0	<1
Tin	ppm	ASTM D5185m	>25	<1	0	<1
Antimony	ppm	ASTM D5185m	>5			0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	7
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		<1	0	<1
Calcium	ppm	ASTM D5185m		7	22	19
Phosphorus	ppm	ASTM D5185m		485	387	350
Zinc	ppm	ASTM D5185m		3	2	14
Sulfur	ppm	ASTM D5185m		2082	11918	10299
CONTAMINANT	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	44	32	38
Sodium	ppm	ASTM D5185m		0	6	4
Potassium	ppm	ASTM D5185m	>20	1	0	<1
FLUID CLEANLI	INESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	17797	▲ 30461	▲ 53666
Particles >6µm		ASTM D7647	>2500	<u>2601</u>	2501	3448
Particles >14μm		ASTM D7647	>640	128	107	59
Particles >21µm		ASTM D7647	>160	21	28	10
Particles >38μm		ASTM D7647	>40	1	2	0
Particles >71µm		ASTM D7647	>10	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/16	2 1/19/14	<u>22/19/14</u>	<u>\$\text{23}\19\13\$</u>



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06175437

Unique Number : 11021490

: PCA0118366 Received

: 10 May 2024 **Tested** Diagnosed

: 13 May 2024

: 14 May 2024 - Don Baldridge

Test Package : IND 2 (Additional Tests: PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369. st - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

ryan.schmid@kraftheinz.com

KraftHeinz - New Ulm - Plant 8302

2525 S BRIDGE STREET

Contact: RYAN SCHMID

NEW ULM, MN

T: (507)568-0338

F: (507)354-7927

US 56073