


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL


Area
(55225Z) Walgreens - Tractor
 Machine Id
[Walgreens - Tractor] 136A63357
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS
Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0119062	PCA0119062	PCA0105870
Sample Date	Client Info			06 May 2024	06 May 2024	24 Jan 2024
Machine Age	mls Client Info			102505	102505	80455
Oil Age	mls Client Info			102505	102505	25000
Oil Changed	Client Info			N/A	N/A	Oil Added
Sample Status				NORMAL	---	ABNORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	39	49	22
Chromium	ppm	ASTM D5185m	>5	3	4	2
Nickel	ppm	ASTM D5185m	>2	<1	<1	2
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>3	<1	0	<1
Aluminum	ppm	ASTM D5185m	>30	28	38	24
Lead	ppm	ASTM D5185m	>30	<1	<1	<1
Copper	ppm	ASTM D5185m	>150	98	59	▲ 159
Tin	ppm	ASTM D5185m	>5	2	3	2
Vanadium	ppm	ASTM D5185m		<1	<1	<1
Cadmium	ppm	ASTM D5185m		<1	<1	0




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	3	4	3
Barium	ppm	ASTM D5185m	0	2	2	0
Molybdenum	ppm	ASTM D5185m	50	63	61	57
Manganese	ppm	ASTM D5185m	0	1	2	2
Magnesium	ppm	ASTM D5185m	950	878	871	857
Calcium	ppm	ASTM D5185m	1050	1190	1238	1083
Phosphorus	ppm	ASTM D5185m	995	971	988	958
Zinc	ppm	ASTM D5185m	1180	1159	1168	1194
Sulfur	ppm	ASTM D5185m	2600	2500	2505	2712

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5	6	4
Sodium	ppm	ASTM D5185m		0	<1	3
Potassium	ppm	ASTM D5185m	>20	70	96	56

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.7	1	0.5
Nitration	Abs/cm	*ASTM D7624	>20	9.2	9.7	8.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.9	21.7	20.0

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.4	19.0	16.6
Base Number (BN)	mg KOH/g	ASTM D2896		6.1	7.2	8.1





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.3	11.4

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0119062 **Received** : 10 May 2024
Lab Number : 06176479 **Tested** : 13 May 2024
Unique Number : 11022532 **Diagnosed** : 13 May 2024 - Wes Davis
Test Package : FLEET

Transervice - Shop 1361 - Berkeley-Windsor
 4400 State Road 19
 Windsor, WI
 US 53598
 Contact: Mike Hurda
 mhurda@transervice.com
 T: (608)846-2726
 F: (608)846-0389

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)