

## **OIL ANALYSIS REPORT**

### Area **ELGIN** NOT GIVEN PCA0125343 (S/N NO INFO ON SIF/BOTTLE) **Hydraulic System**

{not provided} (--- GAL)

### DIAGNOSIS

#### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The condition of the oil is acceptable for the time in service.



Sample Rating Trend



SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0125343		
Sample Date		Client Info		13 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	6		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	4		
Tin	ppm	ASTM D5185m	>20	1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		12		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		1		
Calcium	ppm	ASTM D5185m		19		
Phosphorus	ppm	ASTM D5185m		577		
Zinc	ppm	ASTM D5185m		12		
Sulfur	ppm	ASTM D5185m		1936		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m		0		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.05	NEG		

Free Water


scalar \*Visual

Contact/Location: STEVE METCALF - ELGPIN

NEG



# **OIL ANALYSIS REPORT**



FLUID PROP	PERTIES	s method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D445		44.0			
SAMPLE IM/	AGES	method	limit/base	current	history1	history2	
Color				no image	no image	no image	
Bottom				no image	no image	no image	
20110							
GRAPHS							
Ferrous Alloys							
9 - iron							
8 - nickel							
6-							
4							
3							
1-							
May13/24			May13/24				
			May				
Non-ferrous Me	tals						
9 - copper 8 - tin							
7-							
6 - 5 -							
4							
2 -							
0							
May13/24			May13/24				
≥ Viscosity @ 40°	С		M				
Abnormal							
50							
18-							
16 - 14 -							
12 -							
40 - Abnormal							
38							
May13/24			May13/24				
2			2				
VearCheck USA - 501 Madison Ave., Cary, NC 27513   PCA0125343 Received : 13 May 2024   6178012 Tested : 14 May 2024   1029338 Diagnosed : 14 May 2024 - Wes Davis				les Davis	ELGIN DIE MOLD 14N002 PRAIRIE ST PINGREE GROVE, IL US 60140		



Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** 

Test Package : IND 1

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Contact/Location: STEVE METCALF - ELGPIN

T:

F:

Contact: STEVE METCALF

pm@elgindiemold.com