


OIL ANALYSIS REPORT

ELGIN

NOT GIVEN PCA0125341 (S/N NO INFO ON SIF/BOTTLE)

Hydraulic System

{not provided} (--- GAL)



DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in

				May2024		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0125341		
Sample Date		Client Info		13 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed	1115	Client Info		N/A		
Sample Status		Ciletit IIIIO		NORMAL		
CONTAMINAT	ION	method	limit/base			history2
Water	ION	WC Method	>0.05	current NEG	history1	1115101 y 2
WEAR METAL	0	method	limit/base		hiotory1	history?
WEAR METAL	S	method	iiiiii/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	13		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	8		
Tin	ppm	ASTM D5185m	>20	2		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
4 D D I T V / T O	la la constant					
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		12		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		9		
Phosphorus	ppm	ASTM D5185m		563		
Zinc	ppm	ASTM D5185m		14		
Sulfur	ppm	ASTM D5185m		1964		
CONTAMINAN	TC	mathad	limit/base	Olive ont	history1	history?
		method		current	HISTOLAL	history2
Silicon	ppm	ASTM D5185m	>15			
Sodium	ppm	ASTM D5185m	00	1		
Potassium	ppm	ASTM D5185m	>20	0		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
0.11		*Visual	NONE	NONE		
Silt	scalar	11000				
Debris	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Debris Sand/Dirt	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE		
Debris Sand/Dirt Appearance	scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NORML	NONE NONE NORML		
Debris Sand/Dirt Appearance Odor	scalar scalar scalar	*Visual *Visual *Visual	NONE NORML	NONE NONE NORML NORML		





OIL ANALYSIS REPORT






GRAPHS









Certificate 12367

Laboratory

Unique Number : 11029351

Sample No. : PCA0125341 Lab Number : 06178025

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 13 May 2024 Tested

Diagnosed

: 14 May 2024 : 14 May 2024 - Wes Davis

ELGIN DIE MOLD 14N002 PRAIRIE ST PINGREE GROVE, IL US 60140 Contact: STEVE METCALF pm@elgindiemold.com

Test Package : IND 1 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: