

# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL

934021 Component Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (--- GAL)

## DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Machine Id

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the fluid.

### Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORM	<b>/IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0120185		
Sample Date		Client Info		21 May 2024		
Machine Age	hrs	Client Info		2261		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>220	59		
Chromium	ppm	ASTM D5185m	>2	<1		
Nickel	ppm	ASTM D5185m	>5	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>5	<1		
Aluminum	ppm	ASTM D5185m	>75	21		
Lead	ppm	ASTM D5185m	>95	42		
Copper	ppm	ASTM D5185m	>60	22		
Tin	ppm	ASTM D5185m	>10	5		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		65		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		128		
Phosphorus	ppm	ASTM D5185m		199		
Zinc	ppm	ASTM D5185m		20		
Sulfur	ppm	ASTM D5185m		1840		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	7		
Sodium	ppm	ASTM D5185m		4		
Potassium	ppm	ASTM D5185m	>20	6		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
	scalar	*Visual	NONE	NONE		
Silt	000.00					
Silt Debris	scalar	*Visual	NONE	NONE		
		*Visual *Visual	NONE	NONE		
Debris	scalar					
Debris Sand/Dirt	scalar scalar	*Visual	NONE	NONE		
Debris Sand/Dirt Appearance	scalar scalar scalar	*Visual *Visual	NONE NORML	NONE NORML		



# **OIL ANALYSIS REPORT**



FLUID PROP	ERTIES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D445	34	31.9		
SAMPLE IMA	GES	method	limit/base	current	history1	history
Color				no image	no image	no image
				no image	no image	no image
Bottom				no image	no image	no image
Dottom				no inago	line intege	
GRAPHS						
Ferrous Alloys						
50 - chromium						
40 nickel						
Ē 30-						
20 -						
10						
0			5			
May21/24			May21/24			
Non-ferrous Met	als		2			
45 copper			,			
40 35						
30 -						
E 25 - 20 - 20 - 20 - 20 - 20 - 20 - 20 -						
15						
10						
5 -		*****				
0 24 0			/24			
May21/24			May21/24			
Viscosity @ 40°C	2					
39 38 Abormal						
30 Abnormal 37						
36						
() 35 0 34 - Base 1 34 - Base						
32						
30 - Abnormal						
29			24			
May21/24			May21/24			
~			~			
: WearCheck USA - 5				GFL Env	rironmental - 836 - K	
: GFL0120185	Recei		May 2024			st Truman Re
· 06189642	Tooto					aneae City
: 06189642 : 11046394	Teste Diagn		May 2024 May 2024 - V	Ves Davis	ĸ	ansas City, I US 641

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: GFL823,834,836,837,840 - Loyce Stewart - GFL836

T:

F: