


# **OIL ANALYSIS REPORT**





# **DEGRADATION**

### **DIAGNOSIS**

#### Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

Light fuel dilution occurring.


#### Fluid Condition

The BN level is low. The condition of the oil is acceptable for the time in service.


•						
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0122495	GFL0117664	GFL010872
Sample Date		Client Info		21 May 2024	09 Apr 2024	05 Jan 2024
Machine Age	hrs	Client Info		20833	20700	20313
Oil Age	hrs	Client Info		20247	20247	20247
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				ABNORMAL	SEVERE	SEVERE
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	.S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	72	61	30
Chromium	ppm	ASTM D5185m	>20	3	2	<1
Nickel	ppm	ASTM D5185m	>2	1	0	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	6	6	2
Lead	ppm	ASTM D5185m	>40	13	8	4
Copper	ppm	ASTM D5185m	>330	18	6	2
Tin	ppm	ASTM D5185m	>15	2	1	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	6	2	0
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	46	55	52
Manganese	ppm	ASTM D5185m	0	<1	1	0
Magnesium	ppm	ASTM D5185m	1010	688	914	843
Calcium	ppm	ASTM D5185m	1070	835	1045	944
Phosphorus	ppm	ASTM D5185m	1150	761	1023	919
Zinc	ppm	ASTM D5185m	1270	1050	1238	1107
Sulfur	ppm	ASTM D5185m	2060	2329	3233	2761
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	7	6	4
Sodium	ppm	ASTM D5185m		5	4	4
Potassium	ppm	ASTM D5185m	>20	3	1	2
Fuel	%	ASTM D3524	>3.0	<u>^</u> 2.5	<b>▲</b> 6.6	▲ 10.1
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>6	5	4.4	2.4
Nitration	Abs/cm	*ASTM D7624	>20	15.1	15.4	10.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	33.2	29.6	22.9
FLUID DEGRAI	DATION	method	limit/base	current	history1	history2
FLUID DEGRAI	DATION Abs/.1mm	method *ASTM D7414	limit/base >25	current 25.9	history1 23.5	history2 18.3
		*ASTM D7414	>25			




# **OIL ANALYSIS REPORT**



/_/
Annual an








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPI	ERITES	method	limit/base	current	history1	history
Visc @ 100°C	cSt	ASTM D445	15.4	13.2	14.4	12.5

#### **GRAPHS**













Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06190326

: GFL0122495 Unique Number : 11047078

Received **Tested** Diagnosed

: 24 May 2024 : 30 May 2024

: 30 May 2024 - Jonathan Hester

Sterling Heights, MI US 48313 Contact: Frank Wolak fwolak@gflenv.com T: (586)825-9514

GFL Environmental - 415 - Michigan East

Certificate 12367

Test Package : FLEET ( Additional Tests: PercentFuel ) To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: GFL415 [WUSCAR] 06190326 (Generated: 05/30/2024 13:48:10) Rev: 1

Submitted By: Frank Wolak

6200 Elmridge