



OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
 (H607954) YARD UNIT/STORAGE TRAILER
 Machine Id
425107
 Component
Diesel Engine
 Fluid
 {not provided} (5 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

Metal levels are typical for a components first oil change.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0110368	---	---
Sample Date	Client Info		16 May 2024	---	---
Machine Age	hrs	Client Info	1902	---	---
Oil Age	hrs	Client Info	1902	---	---
Oil Changed	Client Info		Changed	---	---
Sample Status			NORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	---	---
Water	WC Method	>0.2	NEG	---	---
Glycol	WC Method		NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	7	---
Chromium	ppm	ASTM D5185m	>20	0	---
Nickel	ppm	ASTM D5185m	>4	0	---
Titanium	ppm	ASTM D5185m		0	---
Silver	ppm	ASTM D5185m	>3	<1	---
Aluminum	ppm	ASTM D5185m	>20	2	---
Lead	ppm	ASTM D5185m	>40	1	---
Copper	ppm	ASTM D5185m	>330	<1	---
Tin	ppm	ASTM D5185m	>15	0	---
Vanadium	ppm	ASTM D5185m		0	---
Cadmium	ppm	ASTM D5185m		0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		9	---
Barium	ppm	ASTM D5185m		0	---
Molybdenum	ppm	ASTM D5185m		68	---
Manganese	ppm	ASTM D5185m		<1	---
Magnesium	ppm	ASTM D5185m		897	---
Calcium	ppm	ASTM D5185m		1018	---
Phosphorus	ppm	ASTM D5185m		967	---
Zinc	ppm	ASTM D5185m		1188	---
Sulfur	ppm	ASTM D5185m		3176	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5	---
Sodium	ppm	ASTM D5185m		3	---
Potassium	ppm	ASTM D5185m	>20	<1	---

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3	---
Nitration	Abs/cm	*ASTM D7624	>20	6.3	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.7	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.0	---
Base Number (BN)	mg KOH/g	ASTM D2896		8.9	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	13.5	---	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0110368 **Received** : 24 May 2024
Lab Number : **06191648** **Tested** : 29 May 2024
Unique Number : 11048400 **Diagnosed** : 29 May 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 031 - Greenville/Spartanburg
 1635 Antioch Church Rd
 Piedmont, SC
 US 29673
 Contact: TECHNICIAN ACCOUNT
 catherine.anastasio@wearcheck.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)