




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**923056**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0116708</b>	GFL0116687	GFL0100874
Sample Date	Client Info		<b>23 May 2024</b>	14 May 2024	02 Jan 2024
Machine Age	mls	Client Info	<b>509168</b>	497595	497595
Oil Age	mls	Client Info	<b>497595</b>	497595	2400
Oil Changed	Client Info		<b>Changed</b>	Not Changd	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>61</b>	61	24
Chromium	ppm	ASTM D5185m >20	<b>2</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m >2	<b>1</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	2	<1
Lead	ppm	ASTM D5185m >40	<b>6</b>	4	<1
Copper	ppm	ASTM D5185m >330	<b>5</b>	3	2
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	<1	1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>5</b>	6	8
Barium	ppm	ASTM D5185m 0	<b>&lt;1</b>	0	<1
Molybdenum	ppm	ASTM D5185m 60	<b>63</b>	63	56
Manganese	ppm	ASTM D5185m 0	<b>1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>920</b>	904	824
Calcium	ppm	ASTM D5185m 1070	<b>1143</b>	1056	1013
Phosphorus	ppm	ASTM D5185m 1150	<b>1014</b>	1001	987
Zinc	ppm	ASTM D5185m 1270	<b>1219</b>	1195	1113
Sulfur	ppm	ASTM D5185m 2060	<b>3093</b>	3064	2828

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>5</b>	4	2
Sodium	ppm	ASTM D5185m	<b>2</b>	2	4
Potassium	ppm	ASTM D5185m >20	<b>5</b>	0	0

## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>3.1</b>	2.3	1.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.8</b>	9.9	6.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>24.6</b>	23.1	19.2


## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>16.7</b>	16.3	12.8
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.0</b>	7.7	8.9




# OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


PARAMETER	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.2	13.9

## GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0116708  
 Lab Number : 06191852  
 Unique Number : 11048604  
 Test Package : FLEET

GFL Environmental - 419 - Metro Saginaw  
 6950 N Michigan  
 Saginaw, MI  
 US 48604

Contact: Jeremy Hines  
 jhines@gflenv.com  
 T: (800)684-1277  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)