




# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id

**427117**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1    | history2    |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info |             | <b>GFL0116017</b>  | GFL0092883  | GFL0097460  |
| Sample Date   | Client Info |             | <b>16 May 2024</b> | 03 Jan 2024 | 31 Oct 2023 |
| Machine Age   | hrs         | Client Info | <b>12136</b>       | 11561       | 11409       |
| Oil Age       | hrs         | Client Info | <b>10018</b>       | 10018       | 10018       |
| Oil Changed   | Client Info |             | <b>N/A</b>         | N/A         | N/A         |
| Sample Status |             |             | <b>NORMAL</b>      | NORMAL      | NORMAL      |

## CONTAMINATION

|        | method    | limit/base | current        | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel   | WC Method | >5         | <b>&lt;1.0</b> | <1.0     | <1.0     |
| Water  | WC Method | >0.2       | <b>NEG</b>     | NEG      | NEG      |
| Glycol | WC Method |            | <b>NEG</b>     | NEG      | NEG      |

## WEAR METALS

|          | method | limit/base       | current      | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron     | ppm    | ASTM D5185m >110 | <b>27</b>    | 6        | 26       |
| Chromium | ppm    | ASTM D5185m >4   | <b>2</b>     | 0        | <1       |
| Nickel   | ppm    | ASTM D5185m >2   | <b>&lt;1</b> | 0        | 0        |
| Titanium | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |
| Silver   | ppm    | ASTM D5185m >2   | <b>1</b>     | 0        | 0        |
| Aluminum | ppm    | ASTM D5185m >25  | <b>6</b>     | 1        | 6        |
| Lead     | ppm    | ASTM D5185m >45  | <b>5</b>     | 2        | 8        |
| Copper   | ppm    | ASTM D5185m >85  | <b>2</b>     | 0        | 1        |
| Tin      | ppm    | ASTM D5185m >4   | <b>1</b>     | 0        | <1       |
| Vanadium | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | <1       |
| Cadmium  | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |

## ADDITIVES

|            | method | limit/base       | current      | history1 | history2 |
|------------|--------|------------------|--------------|----------|----------|
| Boron      | ppm    | ASTM D5185m 0    | <b>6</b>     | 6        | 6        |
| Barium     | ppm    | ASTM D5185m 0    | <b>1</b>     | 0        | 0        |
| Molybdenum | ppm    | ASTM D5185m 60   | <b>86</b>    | 56       | 64       |
| Manganese  | ppm    | ASTM D5185m 0    | <b>&lt;1</b> | 0        | <1       |
| Magnesium  | ppm    | ASTM D5185m 1010 | <b>1304</b>  | 901      | 965      |
| Calcium    | ppm    | ASTM D5185m 1070 | <b>1457</b>  | 1034     | 1223     |
| Phosphorus | ppm    | ASTM D5185m 1150 | <b>1404</b>  | 944      | 1107     |
| Zinc       | ppm    | ASTM D5185m 1270 | <b>1685</b>  | 1247     | 1283     |
| Sulfur     | ppm    | ASTM D5185m 2060 | <b>4160</b>  | 2886     | 3017     |

## CONTAMINANTS

|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >30 | <b>7</b> | 2        | 6        |
| Sodium    | ppm    | ASTM D5185m     | <b>7</b> | 2        | 6        |
| Potassium | ppm    | ASTM D5185m >20 | <b>7</b> | 4        | 15       |

## INFRA-RED




|           | method   | limit/base      | current     | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot %    | %        | *ASTM D7844 >3  | <b>0.7</b>  | 0.3      | 0.7      |
| Nitration | Abs/cm   | *ASTM D7624 >20 | <b>10.5</b> | 7.8      | 11.8     |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | <b>20.9</b> | 18.7     | 22.9     |

## FLUID DEGRADATION

|                  | method   | limit/base      | current     | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm | *ASTM D7414 >25 | <b>16.9</b> | 14.6     | 18.8     |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8  | <b>7.2</b>  | 8.0      | 6.7      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Yellow Metal     | scalar | *Visual    | NONE    | NONE     | NONE     |
| Precipitate      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Silt             | scalar | *Visual    | NONE    | NONE     | NONE     |
| Debris           | scalar | *Visual    | NONE    | NONE     | NONE     |
| Sand/Dirt        | scalar | *Visual    | NONE    | NONE     | NONE     |
| Appearance       | scalar | *Visual    | NORML   | NORML    | NORML    |
| Odor             | scalar | *Visual    | NORML   | NORML    | NORML    |
| Emulsified Water | scalar | *Visual    | >0.2    | NEG      | NEG      |
| Free Water       | scalar | *Visual    |         | NEG      | NEG      |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 100°C     | cSt    | ASTM D445  | 15.4    | 13.1     | 13.2     |

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0116017  
**Lab Number** : 06191883  
**Unique Number** : 11048635  
**Test Package** : FLEET  
**Received** : 28 May 2024  
**Tested** : 29 May 2024  
**Diagnosed** : 30 May 2024 - Sean Felton

**GFL Environmental - 641 - Alpena**  
 1241 KING SETTLEMENT RD  
 ALPENA, MI  
 US 49707  
 Contact: DYLAN TOLAN  
 dylan.tolan@gflenv.com  
 T: (989)854-7203  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)