


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(65234Z) Walgreens - Tractor
 Machine Id
[Walgreens - Tractor] 136A624210
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0121329	PCA0106581	---
Sample Date	Client Info			16 May 2024	14 Feb 2024	---
Machine Age	mls	Client Info		94171	61964	---
Oil Age	mls	Client Info		50000	50000	---
Oil Changed	Client Info			N/A	Changed	---
Sample Status				NORMAL	ABNORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	---
Water	WC Method	>0.2		NEG	NEG	---
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	40	73	---
Chromium	ppm	ASTM D5185m	>5	3	5	---
Nickel	ppm	ASTM D5185m	>2	<1	1	---
Titanium	ppm	ASTM D5185m		0	0	---
Silver	ppm	ASTM D5185m	>3	0	0	---
Aluminum	ppm	ASTM D5185m	>30	36	109	---
Lead	ppm	ASTM D5185m	>30	<1	3	---
Copper	ppm	ASTM D5185m	>150	69	▲ 205	---
Tin	ppm	ASTM D5185m	>5	1	6	---
Vanadium	ppm	ASTM D5185m		<1	<1	---
Cadmium	ppm	ASTM D5185m		0	0	---





ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<1	36	---
Barium	ppm	ASTM D5185m	0	0	<1	---
Molybdenum	ppm	ASTM D5185m	50	58	40	---
Manganese	ppm	ASTM D5185m	0	2	5	---
Magnesium	ppm	ASTM D5185m	950	937	599	---
Calcium	ppm	ASTM D5185m	1050	1392	1810	---
Phosphorus	ppm	ASTM D5185m	995	958	751	---
Zinc	ppm	ASTM D5185m	1180	1189	915	---
Sulfur	ppm	ASTM D5185m	2600	2414	1735	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	4	8	---
Sodium	ppm	ASTM D5185m		3	8	---
Potassium	ppm	ASTM D5185m	>20	72	251	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.6	0.7	---
Nitration	Abs/cm	*ASTM D7624	>20	9.0	11.2	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.5	23.5	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.9	27.0	---
Base Number (BN)	mg KOH/g	ASTM D2896		7.0	5.7	---





OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.5	10.7

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0121329 **Received** : 29 May 2024
Lab Number : **06193518** **Tested** : 30 May 2024
Unique Number : 11050270 **Diagnosed** : 30 May 2024 - Wes Davis
Test Package : FLEET

Transervice - Shop 1369 - Berkeley-Waxahachie
 710 Ovilla Road
 Waxahachie, TX
 US 75167
 Contact: Robert Beal
 rbeal@transervice.com
 T: (972)923-9928
 F: (972)923-9919

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)