


# **OIL ANALYSIS REPORT**

## Sample Rating Trend



NORMAL



Machine Id
2515
Component
Diesel Engine

## PETRO CANADA DURON SHP 15W40 (11 GAL)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.


## **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


| GAL)             |          | ir2016 Jan20 | 17 Nov2017 May2018 | Jul2019 Oct2020 Aug2022 | Jct2023     |              |
|------------------|----------|--------------|--------------------|-------------------------|-------------|--------------|
| SAMPLE INFOR     | MATION   | method       | limit/base         | current                 | history1    | history2     |
| Sample Number    |          | Client Info  |                    | GFL0071992              | GFL0072135  | GFL0072033   |
| Sample Date      |          | Client Info  |                    | 27 May 2024             | 12 Mar 2024 | 12 Dec 2023  |
| Machine Age      | hrs      | Client Info  |                    | 28742                   | 28181       | 624096       |
| Oil Age          | hrs      | Client Info  |                    | 592                     | 600         | 0            |
| Oil Changed      |          | Client Info  |                    | Changed                 | Changed     | Changed      |
| Sample Status    |          |              |                    | NORMAL                  | ABNORMAL    | ABNORMAL     |
| CONTAMINAT       | ION      | method       | limit/base         | current                 | history1    | history2     |
| Fuel             |          | WC Method    | >3.0               | <1.0                    | <1.0        | <1.0         |
| Water            |          | WC Method    | >0.2               | NEG                     | NEG         | NEG          |
| Glycol           |          | WC Method    |                    | NEG                     | NEG         | NEG          |
| WEAR METAL       | _S       | method       | limit/base         | current                 | history1    | history2     |
| Iron             | ppm      | ASTM D5185m  | >165               | 19                      | 23          | 12           |
| Chromium         | ppm      | ASTM D5185m  | >5                 | <1                      | <1          | <1           |
| Nickel           | ppm      | ASTM D5185m  | >4                 | 0                       | <1          | 0            |
| Titanium         | ppm      | ASTM D5185m  | >2                 | 0                       | <1          | 0            |
| Silver           | ppm      | ASTM D5185m  | >2                 | 0                       | 0           | 0            |
| Aluminum         | ppm      | ASTM D5185m  | >20                | 3                       | 2           | 2            |
| Lead             | ppm      | ASTM D5185m  | >150               | 4                       | 4           | 8            |
| Copper           | ppm      | ASTM D5185m  | >90                | 31                      | <u> </u>    | <b>A</b> 80  |
| Tin              | ppm      | ASTM D5185m  | >5                 | <1                      | <1          | <1           |
| Vanadium         | ppm      | ASTM D5185m  |                    | 0                       | 0           | <1           |
| Cadmium          | ppm      | ASTM D5185m  |                    | 0                       | 0           | 0            |
| ADDITIVES        |          | method       | limit/base         | current                 | history1    | history2     |
| Boron            | ppm      | ASTM D5185m  | 0                  | 3                       | 3           | 7            |
| Barium           | ppm      | ASTM D5185m  | 0                  | 0                       | 0           | 0            |
| Molybdenum       | ppm      | ASTM D5185m  | 60                 | 65                      | 67          | 70           |
| Manganese        | ppm      | ASTM D5185m  | 0                  | 0                       | <1          | 0            |
| Magnesium        | ppm      | ASTM D5185m  | 1010               | 951                     | 989         | 956          |
| Calcium          | ppm      | ASTM D5185m  | 1070               | 1099                    | 1138        | 1055         |
| Phosphorus       | ppm      | ASTM D5185m  | 1150               | 967                     | 1063        | 894          |
| Zinc             | ppm      | ASTM D5185m  | 1270               | 1247                    | 1323        | 1254         |
| Sulfur           | ppm      | ASTM D5185m  | 2060               | 2720                    | 2814        | 2770         |
| CONTAMINAN       |          | method       | limit/base         | current                 | history1    | history2     |
| Silicon          | ppm      | ASTM D5185m  | >35                | 6                       | 8           | 12           |
| Sodium           | ppm      | ASTM D5185m  |                    | 22                      | 64          | <u>^</u> 264 |
| Potassium        | ppm      | ASTM D5185m  |                    | 0                       | 3           | 2            |
| INFRA-RED        |          | method       | limit/base         | current                 | history1    | history2     |
| Soot %           | %        | *ASTM D7844  | >7.5               | 0.6                     | 0.7         | 0.4          |
| Nitration        | Abs/cm   | *ASTM D7624  | >20                | 10.6                    | 10.8        | 10.1         |
| Sulfation        | Abs/.1mm | *ASTM D7415  | >30                | 21.7                    | 22.6        | 21.7         |
| FLUID DEGRA      | DATION   | method       | limit/base         | current                 | history1    | history2     |
| Oxidation        | Abs/.1mm | *ASTM D7414  | >25                | 18.6                    | 19.8        | 18.1         |
| Base Number (BN) | mg KOH/g | ASTM D2896   | 9.8                | 6.5                     | 6.6         | 7.1          |



## **OIL ANALYSIS REPORT**










| VISUAL                  |        | method  | limit/base | current | history1 | history2 |
|-------------------------|--------|---------|------------|---------|----------|----------|
| White Metal             | scalar | *Visual | NONE       | NONE    | NONE     | NONE     |
| Yellow Metal            | scalar | *Visual | NONE       | NONE    | NONE     | NONE     |
| Precipitate             | scalar | *Visual | NONE       | NONE    | NONE     | NONE     |
| Silt                    | scalar | *Visual | NONE       | NONE    | NONE     | NONE     |
| Debris                  | scalar | *Visual | NONE       | NONE    | NONE     | NONE     |
| Sand/Dirt               | scalar | *Visual | NONE       | NONE    | NONE     | NONE     |
| Appearance              | scalar | *Visual | NORML      | NORML   | NORML    | NORML    |
| Odor                    | scalar | *Visual | NORML      | NORML   | NORML    | NORML    |
| <b>Emulsified Water</b> | scalar | *Visual | >0.2       | NEG     | NEG      | NEG      |
| Free Water              | scalar | *Visual |            | NEG     | NEG      | NEG      |


| FLUID PROPE  | KIIES | method    |      |      | history1 | history2 |
|--------------|-------|-----------|------|------|----------|----------|
| Visc @ 100°C | cSt   | ASTM D445 | 15.4 | 13.5 | 13.7     | 13.4     |

### **GRAPHS**













Certificate 12367

Laboratory Sample No. Unique Number : 11057305

Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : GFL0071992 Lab Number : 06195182

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Received : 30 May 2024 **Tested** : 31 May 2024

Diagnosed : 31 May 2024 - Wes Davis

GFL Environmental - 094 - Cedartown 2097 Buchanan Highway

> Cedartown, GA US 30125

Contact: WILLIAM FOSTER william.foster@gflenv.com T: (800)207-6618

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)