




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**433003**

Component  
**Natural Gas Engine**

Fluid  
**PETRO CANADA DURON GEO LD 15W40 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0120149</b>	GFL0117215	GFL0117246
Sample Date	Client Info		<b>28 May 2024</b>	15 May 2024	02 May 2024
Machine Age	hrs	Client Info	<b>3608</b>	3463	3298
Oil Age	hrs	Client Info	<b>1200</b>	0	0
Oil Changed	Client Info		<b>Changed</b>	Not Changd	Not Changd
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	<b>4</b>	13	12
Chromium	ppm	ASTM D5185m >4	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m >2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >9	<b>4</b>	2	2
Lead	ppm	ASTM D5185m >30	<b>&lt;1</b>	2	<1
Copper	ppm	ASTM D5185m >35	<b>9</b>	2	<1
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	0	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 50	<b>6</b>	10	17
Barium	ppm	ASTM D5185m 5	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>50</b>	51	56
Manganese	ppm	ASTM D5185m 0	<b>0</b>	1	<1
Magnesium	ppm	ASTM D5185m 560	<b>551</b>	574	580
Calcium	ppm	ASTM D5185m 1510	<b>1531</b>	1661	1719
Phosphorus	ppm	ASTM D5185m 780	<b>687</b>	800	785
Zinc	ppm	ASTM D5185m 870	<b>929</b>	1019	1046
Sulfur	ppm	ASTM D5185m 2040	<b>2621</b>	3025	2941

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	<b>7</b>	6	4
Sodium	ppm	ASTM D5185m	<b>23</b>	<1	29
Potassium	ppm	ASTM D5185m >20	<b>0</b>	0	2

## INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	<b>0.2</b>	0	0
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.2</b>	10.2	11.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>22.5</b>	19.3	22.8

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.3</b>	16.4	18.0
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	<b>5.3</b>	5.2	4.7







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.1	13.6	13.9

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0120149      **Received** : 30 May 2024  
**Lab Number** : 06195252      **Tested** : 31 May 2024  
**Unique Number** : 11057375      **Diagnosed** : 31 May 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 836 - Kansas City Hauling**  
 7801 East Truman Road  
 Kansas City, MO  
 US 64126  
 Contact: Loyce Stewart  
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)