

OIL ANALYSIS REPORT


Area
Plymouth & Brockton

Machine Id
414

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (39 QTS)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0109973	PCA0104429	PCA0104555
Sample Date	Client Info			16 May 2024	02 Mar 2024	12 Jan 2024
Machine Age	mls	Client Info		572651	562656	552380
Oil Age	mls	Client Info		24000	12000	24000
Oil Changed	Client Info			Changed	Not Changd	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>3.0		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	76	35	77
Chromium	ppm	ASTM D5185m	>20	4	2	3
Nickel	ppm	ASTM D5185m	>2	<1	0	0
Titanium	ppm	ASTM D5185m	>2	<1	0	<1
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>20	7	4	12
Lead	ppm	ASTM D5185m	>40	7	1	18
Copper	ppm	ASTM D5185m	>330	3	5	2
Tin	ppm	ASTM D5185m	>15	2	0	1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	9	8	9
Barium	ppm	ASTM D5185m	0	2	0	<1
Molybdenum	ppm	ASTM D5185m	60	79	63	67
Manganese	ppm	ASTM D5185m	0	<1	<1	1
Magnesium	ppm	ASTM D5185m	1010	1088	965	940
Calcium	ppm	ASTM D5185m	1070	1288	1116	1195
Phosphorus	ppm	ASTM D5185m	1150	1352	966	1044
Zinc	ppm	ASTM D5185m	1270	1455	1203	1290
Sulfur	ppm	ASTM D5185m	2060	3489	3303	2674

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	14	8	21
Sodium	ppm	ASTM D5185m		9	4	5
Potassium	ppm	ASTM D5185m	>20	2	0	<1

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>6	1.6	1.4	2.3
Nitration	Abs/cm	*ASTM D7624	>20	10.9	12.5	16.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.4	24.6	32.7

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.9	22.0	30.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	6.38	8.31	6.12









OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	15.2	13.8	15.3

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0109973 **Received** : 31 May 2024
Lab Number : 06196885 **Tested** : 03 Jun 2024
Unique Number : 11059008 **Diagnosed** : 03 Jun 2024 - Wes Davis
Test Package : MOB 2

PLYMOUTH & BROCKTON
 8 INDUSTRIAL PARK RD
 PLYMOUTH, MA
 US 02360
 Contact: Donald Pelpquin
 Dpelpquin@P-B.com
 T: (508)732-6039
 F: (508)732-6091

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)