




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
427037-587

Component
Diesel Engine

Fluid
CHEVRON DELO 400 XLE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0104714	GFL0104604	GFL0096321
Sample Date	Client Info		30 May 2024	05 Mar 2024	19 Dec 2023
Machine Age	hrs	Client Info	13228	15228	13176
Oil Age	hrs	Client Info	13176	0	0
Oil Changed	Client Info		Not Chngd	Not Chngd	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	48	15	31
Chromium	ppm	ASTM D5185m >20	2	<1	1
Nickel	ppm	ASTM D5185m >4	0	0	0
Titanium	ppm	ASTM D5185m	11	12	10
Silver	ppm	ASTM D5185m >3	0	0	0
Aluminum	ppm	ASTM D5185m >20	6	5	11
Lead	ppm	ASTM D5185m >40	<1	0	<1
Copper	ppm	ASTM D5185m >330	2	<1	1
Tin	ppm	ASTM D5185m >15	0	0	0
Vanadium	ppm	ASTM D5185m	<1	0	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	106	82	61
Barium	ppm	ASTM D5185m	0	0	0
Molybdenum	ppm	ASTM D5185m	58	52	65
Manganese	ppm	ASTM D5185m	<1	<1	<1
Magnesium	ppm	ASTM D5185m	678	719	731
Calcium	ppm	ASTM D5185m	1717	1580	1755
Phosphorus	ppm	ASTM D5185m 760	824	731	685
Zinc	ppm	ASTM D5185m 830	958	847	905
Sulfur	ppm	ASTM D5185m 2770	3435	3304	2737

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<1	4	7
Sodium	ppm	ASTM D5185m	13	10	10
Potassium	ppm	ASTM D5185m >20	8	7	18

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.7	0.4	0.6
Nitration	Abs/cm	*ASTM D7624 >20	13.1	11.0	12.6
Sulfation	Abs/.1mm	*ASTM D7415 >30	28.0	23.1	27.0

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	26.8	19.9	24.2
Base Number (BN)	mg KOH/g	ASTM D2896 10.7	5.3	6.0	5.2







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.9	14.6	13.9

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0104714 **Received** : 04 Jun 2024
Lab Number : 06198803 **Tested** : 05 Jun 2024
Unique Number : 11060926 **Diagnosed** : 06 Jun 2024 - Sean Felton
Test Package : FLEET

GFL Environmental - 624 - Elmira Hauling
 10164 M-32
 Elmira, MI
 US 49730

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact: ANDY GROBASKI
 andyg@americanwaste.org
 T: (989)370-2941
 F: