


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **AUTOCAR 10461**

Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (7 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


iAL)		52017 Oct20	17 Oct2018 Sep2019	Apr2020 Apr2021 Mar2022 8	Sep 2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0116766	GFL0116814	GFL0109049	
Sample Date		Client Info		29 May 2024	13 May 2024	13 Feb 2024	
Machine Age	hrs	Client Info		1589	1589	1487	
Oil Age	hrs	Client Info		0	0	0	
Oil Changed		Client Info		Not Changd	N/A	N/A	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0	<1.0	1.0	
Water		WC Method	>0.2	NEG	NEG	NEG	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METAL	.S	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	13	12	45	
Chromium	ppm	ASTM D5185m	>20	<1	1	4	
Nickel	ppm	ASTM D5185m	>4	0	<1	0	
Titanium	ppm	ASTM D5185m		0	<1	0	
Silver	ppm	ASTM D5185m	>3	0	<1	0	
Aluminum	ppm	ASTM D5185m	>20	2	3	2	
Lead	ppm	ASTM D5185m	>40	0	<1	0	
Copper	ppm	ASTM D5185m	>330	<1	1	2	
Tin	ppm	ASTM D5185m	>15	0	<1	0	
Vanadium	ppm	ASTM D5185m		0	<1	0	
Cadmium	ppm	ASTM D5185m		0	<1	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	8	9	12	
Barium	ppm	ASTM D5185m	0	0	0	<1	
Molybdenum	ppm	ASTM D5185m	60	62	58	60	
Manganese	ppm	ASTM D5185m	0	<1	<1	0	
Magnesium	ppm	ASTM D5185m	1010	930	776	691	
Calcium	ppm	ASTM D5185m	1070	1230	1067	957	
Phosphorus	ppm	ASTM D5185m	1150	1064	973	818	
Zinc	ppm	ASTM D5185m	1270	1304	1116	1010	
Sulfur	ppm	ASTM D5185m	2060	3900	3282	2564	
CONTAMINAN	ITS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	0	4	9	
Sodium	ppm	ASTM D5185m		3	2	0	
Potassium	ppm	ASTM D5185m	>20	2	3	2	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.4	0.4	0.9	
Nitration	Abs/cm	*ASTM D7624	>20	6.0	5.8	9.0	
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.4	17.0	19.1	
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	12.4	12.2	13.9	
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.3	8.1	6.9	
(1)	0 - 0						



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPE	ERTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.4	12.9	13.0	12.1

GRAPHS













Certificate 12367

Laboratory Sample No.

: GFL0116766 Lab Number : 06198855 Unique Number : 11060978

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received **Tested** Diagnosed : 04 Jun 2024 : 05 Jun 2024

: 05 Jun 2024 - Wes Davis

GFL Environmental - 009 - Fairburn 6905 Roosevelt Hwy

Fairburn, GA US 30213

Contact: Eric Jones erjones@gflenv.com T: (678)630-9927

Test Package : FLEET To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: GFL009 [WUSCAR] 06198855 (Generated: 06/05/2024 05:11:22) Rev: 1