

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Machine Id

733020 Component Hydraulic System Fluid

{not provided} (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFOR		method	limit/base	current	nistory i	nistory2
Sample Number		Client Info		GFL0120234		
Sample Date		Client Info		31 May 2024		
Machine Age	hrs	Client Info		1899		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				ATTENTION		
			line it //e e e e		lata ta mut	history O
CONTAMINAT	ION	methoa	limit/base	current	nistory i	nistory2
Water		WC Method	>0.1	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	nnm	ASTM D5185m	>20	0		
Chromium	nnm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	nnm	ASTM D5185m	210	0		
Silver	ppm	ASTM D5185m		0		
Aluminum	nnm	ASTM D5185m	>10	0		
Lead	nnm	ASTM D5185m	>10	0		
Copper	nnm	ASTM D5185m	>75	<1		
Tin	nnm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m	>10	0		
Cadmium	ppm	ASTM D5185m		0		
Gaumum	ppm	ASTIVI DJ TOJIII		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		56		
Calcium	ppm	ASTM D5185m		38		
Phosphorus	ppm	ASTM D5185m		306		
Zinc	ppm	ASTM D5185m		381		
Sulfur	ppm	ASTM D5185m		948		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	<1		
	INESS	method	limit/hase	current	history1	history2
Particles , 4			× 5000	0720	matory	motoryz
Particles >4µIII		ASTM D7647	>0000	2132		
Particles >0µIII			>1000	933		
$ratuctes > 14\mu m$		ASTM D7647	>100	- 101		
Particles >2 1µ11		AGTM D7647	>40	40		
Partialaa 71		ACTM D7647	>10	0		
Cil Clooplinges		ASTIVI D7647	>3	0		
Un Cleaniness		13U 44Ub (C)	>19/1//14	9/1//15		
FLUID DEGRAD	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045		0.38		

Report Id: GFL836 [WUSCAR] 06199054 (Generated: 06/11/2024 17:21:39) Rev: 1

Contact/Location: GFL823,834,836,837,840 - Loyce Stewart - GFL836



OIL ANALYSIS REPORT



GFL Environmental - 836 - Kansas City Hauling 7801 East Truman Road Kansas City, MO US 64126 Contact: Loyce Stewart loyce.stewart@gflenv.com Т: Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F:

Report Id: GFL836 [WUSCAR] 06199054 (Generated: 06/11/2024 17:21:39) Rev: 1

Contact/Location: GFL823,834,836,837,840 - Loyce Stewart - GFL836

14

Acid Number

74 Mav31 21µ

38L

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

NEG

NEG

34.2

Particle Count

no image

no image

no imade

no imade

22

ISC

:1999 Cle

14

4406