


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
2126974
 Component
Diesel Engine
 Fluid
 {not provided} (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0120175	PCA0120178	---
Sample Date	Client Info			04 Jun 2024	21 May 2024	---
Machine Age	mls	Client Info		138529	133970	---
Oil Age	mls	Client Info		5000	40000	---
Oil Changed	Client Info			Changed	Changed	---
Sample Status				NORMAL	ATTENTION	---

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method	>0.2		NEG	NEG	---
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	19	29	---
Chromium	ppm	ASTM D5185m	>20	0	1	---
Nickel	ppm	ASTM D5185m	>4	0	3	---
Titanium	ppm	ASTM D5185m		0	<1	---
Silver	ppm	ASTM D5185m	>3	<1	2	---
Aluminum	ppm	ASTM D5185m	>20	3	5	---
Lead	ppm	ASTM D5185m	>40	<1	3	---
Copper	ppm	ASTM D5185m	>330	59	29	---
Tin	ppm	ASTM D5185m	>15	<1	2	---
Vanadium	ppm	ASTM D5185m		0	<1	---
Cadmium	ppm	ASTM D5185m		0	<1	---



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	<1	---
Barium	ppm	ASTM D5185m		0	1	---
Molybdenum	ppm	ASTM D5185m		61	64	---
Manganese	ppm	ASTM D5185m		1	1	---
Magnesium	ppm	ASTM D5185m		900	970	---
Calcium	ppm	ASTM D5185m		1026	1128	---
Phosphorus	ppm	ASTM D5185m		899	917	---
Zinc	ppm	ASTM D5185m		1167	1249	---
Sulfur	ppm	ASTM D5185m		2685	2967	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5	7	---
Sodium	ppm	ASTM D5185m		14	2	---
Potassium	ppm	ASTM D5185m	>20	4	12	---
Fuel	%	ASTM D3524	>5	<1.0	0.4	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3	0.5	---
Nitration	Abs/cm	*ASTM D7624	>20	8.9	9.6	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.7	20.8	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.3	16.7	---
Base Number (BN)	mg KOH/g	ASTM D2896		5.9	5.8	---





OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	11.0	11.0	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0120175 **Received** : 06 Jun 2024
Lab Number : 06201223 **Tested** : 11 Jun 2024
Unique Number : 11063346 **Diagnosed** : 11 Jun 2024 - Sean Felton
Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel)

PERDUE FARMS - Lewiston
 210 GRIFFINS QUARTER RD
 LEWISTON, NC
 US 27849
 Contact: NELSON WALLACE
 nelson.wallace2@perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: