




OIL ANALYSIS REPORT

Sample Rating Trend



GLYCOL



Machine Id
426079-402318

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels are high.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0120204	GFL0120189	GFL0117207
Sample Date	Client Info	04 Jun 2024	22 May 2024	26 Apr 2024
Machine Age	hrs	2808	2686	2536
Oil Age	hrs	0	0	0
Oil Changed	Client Info	Not Changed	Not Changed	Not Changed
Sample Status		ABNORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	23	43	17
Chromium	ppm ASTM D5185m >20	2	2	<1
Nickel	ppm ASTM D5185m >4	0	<1	0
Titanium	ppm ASTM D5185m	<1	0	0
Silver	ppm ASTM D5185m >3	<1	<1	0
Aluminum	ppm ASTM D5185m >20	3	4	3
Lead	ppm ASTM D5185m >40	<1	6	<1
Copper	ppm ASTM D5185m >330	<1	3	<1
Tin	ppm ASTM D5185m >15	<1	1	<1
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	<1	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	20	5	6
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 60	83	63	62
Manganese	ppm ASTM D5185m 0	<1	<1	<1
Magnesium	ppm ASTM D5185m 1010	902	967	937
Calcium	ppm ASTM D5185m 1070	1089	1147	1122
Phosphorus	ppm ASTM D5185m 1150	1128	971	1029
Zinc	ppm ASTM D5185m 1270	1223	1267	1239
Sulfur	ppm ASTM D5185m 2060	3350	3155	3312

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	17	6	5
Sodium	ppm ASTM D5185m	690	7	5
Potassium	ppm ASTM D5185m >20	4	2	0
Glycol	% *ASTM D2982	NEG	NEG	NEG

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.5	1.5	0.8
Nitration	Abs/cm *ASTM D7624 >20	6.5	14.5	10.8
Sulfation	Abs.1mm *ASTM D7415 >30	18.3	27.6	21.1


FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs.1mm *ASTM D7414 >25	12.7	27.4	19.5
Base Number (BN)	mg KOH/g ASTM D2896 9.8	11.5	5.2	7.0




OIL ANALYSIS REPORT


FT-IR (Direct Trend)




Glycol Contamination



Viscosity @ 100°C



Glycol Contamination




PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.5	12.7

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0120204

Lab Number : 06202318

Unique Number : 11069779

Test Package : FLEET (Additional Tests: Glycol)

Received : 06 Jun 2024

Tested : 11 Jun 2024

Diagnosed : 11 Jun 2024 - Jonathan Hester

GFL Environmental - 836 - Kansas City Hauling

7801 East Truman Road

Kansas City, MO

US 64126

Contact: Loyce Stewart

loyce.stewart@gflenv.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)