

OIL ANALYSIS REPORT

Sample Rating Trend



Area (51448z) Machine Id 136A63378

Diesel Engine

Fluid PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0119322	PCA0105678	
Sample Date		Client Info		03 Jun 2024	31 Aug 2023	
Machine Age	mls	Client Info		139514	92244	
Oil Age	mls	Client Info		0	5000	
Oil Changed		Client Info		N/A	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	
Glycol		WC Method		NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2
Iron		ASTM D5185m	>80	17	58	
Chromium	ppm	ASTM D5185m	>5	1	8	
Nickel	ppm	ASTM D5185m	>0	0	o <1	
Titanium	ppm	ASTM D5185m	>C	0	<1	
Silver	ppm	ASTM D5185m ASTM D5185m	>3	0	< 1	
Aluminum	ppm	ASTM D5185m	>30	9	146	
Lead	ppm	ASTM D5185m	>30	9	<1	
	ppm	ASTM D5185m	>150	12	61	
Copper Tin	ppm	ASTM D5185m	>5	<1	1	
Vanadium	ppm	ASTM D5185m	>0	0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
	ppm			U	-	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	4	4	
Barium	ppm	ASTM D5185m	0	0	0	
Molybdenum	ppm	ASTM D5185m	50	60	60	
Manganese	ppm	ASTM D5185m	0	<1	2	
Magnesium	ppm	ASTM D5185m	950	927	979	
Calcium	ppm	ASTM D5185m	1050	1091	1315	
Phosphorus	ppm	ASTM D5185m	995			
Zina				1028	936	
Zinc	ppm	ASTM D5185m	1180	1239	1236	
Sulfur	ppm					
	ppm	ASTM D5185m	1180	1239	1236	
Sulfur	ppm	ASTM D5185m ASTM D5185m	1180 2600	1239 3600	1236 2526	
Sulfur CONTAMINAN	ppm TS	ASTM D5185m ASTM D5185m method	1180 2600 limit/base	1239 3600 current	1236 2526 history1	
Sulfur CONTAMINAN Silicon	ppm TS ppm	ASTM D5185m ASTM D5185m method ASTM D5185m	1180 2600 limit/base	1239 3600 current 4	1236 2526 history1 8	 history2
Sulfur CONTAMINAN Silicon Sodium	ppm TS ppm ppm	ASTM D5185m ASTM D5185m Method ASTM D5185m ASTM D5185m	1180 2600 limit/base >20	1239 3600 current 4 0	1236 2526 history1 8 4	 history2
Sulfur CONTAMINAN Silicon Sodium Potassium	ppm TS ppm ppm	ASTM D5185m ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m	1180 2600 limit/base >20 >20	1239 3600 current 4 0 12	1236 2526 history1 8 4 292 history1 1	 history2
Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED	ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	1180 2600 limit/base >20 >20 limit/base	1239 3600 current 4 0 12 current	1236 2526 history1 8 4 292 history1	 history2 history2
Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot %	ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844	1180 2600 imit/base >20 >20 imit/base >3	1239 3600 current 4 0 12 current 0.3	1236 2526 history1 8 4 292 history1 1	 history2 history2
Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm TS ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	1180 2600 imit/base >20 >20 imit/base >3 >20	1239 3600 current 4 0 12 current 0.3 6.1	1236 2526 history1 8 4 292 history1 1 1 10.1	 history2 history2
Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm TS ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7844 *ASTM D7624	1180 2600 >20 >20 20 limit/base >3 >20 >20 >3	1239 3600 current 4 0 12 current 0.3 6.1 19.1	1236 2526 history1 8 4 292 history1 1 1 10.1 21.9	 history2 history2
Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRAE	ppm TS ppm ppm ppm ppm % Abs/cm Abs/cm Abs/1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7624 *ASTM D7624	1180 2600 >20 >20 >20 Imit/base >3 >20 >30 >30	1239 3600 current 4 0 12 current 0.3 6.1 19.1 current	1236 2526 history1 8 4 292 history1 1 10.1 21.9 history1	 history2 history2 history2




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	13.0	11.3	

GRAPHS Ferrous Alloys



To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: TSV1377 [WUSCAR] 06202530 (Generated: 06/10/2024 15:35:49) Rev: 1

Certificate 12367

Contact/Location: Shop 1377 Oil Analysis - TSV1377

T:

F:

shop1377@transervice.com