




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(29KK3A)
Machine Id
721012-361637
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0065741	GFL0108096	GFL0102492
Sample Date	Client Info		03 May 2024	31 Jan 2024	29 Dec 2023
Machine Age	hrs	Client Info	0	27793	27642
Oil Age	hrs	Client Info	200	0	0
Oil Changed	Client Info		Changed	N/A	Changed
Sample Status			NORMAL	NORMAL	ABNORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	32	11	45
Chromium	ppm	ASTM D5185m >5	2	<1	2
Nickel	ppm	ASTM D5185m >2	0	<1	0
Titanium	ppm	ASTM D5185m	<1	0	0
Silver	ppm	ASTM D5185m >3	<1	<1	<1
Aluminum	ppm	ASTM D5185m >30	3	2	5
Lead	ppm	ASTM D5185m >30	4	1	2
Copper	ppm	ASTM D5185m >150	85	30	▲ 173
Tin	ppm	ASTM D5185m >5	2	<1	2
Vanadium	ppm	ASTM D5185m	<1	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<1	6	30
Barium	ppm	ASTM D5185m 0	1	0	0
Molybdenum	ppm	ASTM D5185m 60	60	55	50
Manganese	ppm	ASTM D5185m 0	2	1	4
Magnesium	ppm	ASTM D5185m 1010	971	876	667
Calcium	ppm	ASTM D5185m 1070	1298	1165	2098
Phosphorus	ppm	ASTM D5185m 1150	1008	1035	1002
Zinc	ppm	ASTM D5185m 1270	1291	1265	1183
Sulfur	ppm	ASTM D5185m 2060	2922	3089	3319

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	10	8	▲ 31
Sodium	ppm	ASTM D5185m	7	4	6
Potassium	ppm	ASTM D5185m >20	2	1	5

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.3	0.1	0.3
Nitration	Abs/cm	*ASTM D7624 >20	10.4	6.5	9.6
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.0	19.3	22.4


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	19.6	15.6	22.4
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	7.1	8.9	8.4




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.8	14.1

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0065741 **Received** : 14 Jun 2024
Lab Number : **06211108** **Tested** : 19 Jun 2024
Unique Number : 11083972 **Diagnosed** : 19 Jun 2024 - Sean Felton
Test Package : FLEET

GFL Environmental - 823 - Central Missouri Hauling
 24461 Oak Grove Lane
 Sedalia, MO
 US 65301
 Contact: Terry Randolph
 trandolph@gflenv.com
 T: (660)631-2116
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)