


# OIL ANALYSIS REPORT

### Sample Rating Trend



**NORMAL**



Area  
**(65232Z) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A624208**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0120773</b>	PCA0103556	---
Sample Date	Client Info			<b>04 Jun 2024</b>	28 Feb 2024	---
Machine Age	mls	Client Info		<b>94951</b>	62498	---
Oil Age	mls	Client Info		<b>30000</b>	62498	---
Oil Changed	Client Info			<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	ABNORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	<b>29</b>	68	---
Chromium	ppm	ASTM D5185m	>5	<b>2</b>	4	---
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	2	---
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>30	<b>36</b>	166	---
Lead	ppm	ASTM D5185m	>30	<b>0</b>	<1	---
Copper	ppm	ASTM D5185m	>150	<b>31</b>	285	---
Tin	ppm	ASTM D5185m	>5	<b>2</b>	5	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	---
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	---





ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>4</b>	25	---
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	---
Molybdenum	ppm	ASTM D5185m	50	<b>57</b>	42	---
Manganese	ppm	ASTM D5185m	0	<b>2</b>	4	---
Magnesium	ppm	ASTM D5185m	950	<b>919</b>	623	---
Calcium	ppm	ASTM D5185m	1050	<b>1175</b>	1655	---
Phosphorus	ppm	ASTM D5185m	995	<b>958</b>	828	---
Zinc	ppm	ASTM D5185m	1180	<b>1201</b>	988	---
Sulfur	ppm	ASTM D5185m	2600	<b>2616</b>	2045	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<b>5</b>	9	---
Sodium	ppm	ASTM D5185m		<b>3</b>	6	---
Potassium	ppm	ASTM D5185m	>20	<b>84</b>	385	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	0.7	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.2</b>	11.6	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.5</b>	24.0	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>19.0</b>	27.1	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>7.1</b>	5.1	---





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.3	10.7

### GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0120773      **Received** : 17 Jun 2024  
**Lab Number** : 06212845      **Tested** : 19 Jun 2024  
**Unique Number** : 11085709      **Diagnosed** : 19 Jun 2024 - Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1369 - Berkeley-Waxahachie**  
 710 Ovilla Road  
 Waxahachie, TX  
 US 75167  
 Contact: Robert Beal  
 rbeal@transervice.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)