

# **OIL ANALYSIS REPORT**

## Area **MIX ROOM E [99062894] KR-GR-003115 - WEST DUMPER (S/N MIX E - 11513079)** Component

Hydraulic System

AW HYDRAULIC OIL ISO 68 (--- GAL)

### DIAGNOSIS

#### Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. ( Customer Sample Comment: 99062894 )

#### Wear


All component wear rates are normal.

#### Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0128837	PCA0114149	PCA0124747
Sample Date		Client Info		13 Jun 2024	24 May 2024	24 May 2024
Machine Age	nrs	Client Info		0	0	0
Oil Age h	nrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
		and the set	11		Internet	history O
CONTAMINATIC	JN	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
lron p	opm	ASTM D5185m	>20	<1	<1	<1
Chromium p	opm	ASTM D5185m	>20	<1	<1	<1
Nickel p	opm	ASTM D5185m	>20	<1	0	0
Titanium p	opm	ASTM D5185m		<1	0	<1
	opm	ASTM D5185m		<1	0	0
	opm	ASTM D5185m	>20	2	1	2
	opm	ASTM D5185m	>20	_ <1	0	<1
	opm		>20	<1	0	<1
	opm	ASTM D5185m	>20	<1	<1	<1
1-	opm	ASTM D5185m		<1	0	0
	opm	ASTM D5185m		<1	0	0
1			limit/base			
ADDITIVES		method		current	history1	history2
	opm	ASTM D5185m	5	0	0	0
	opm	ASTM D5185m	5	0	0	<1
Molybdenum p	opm	ASTM D5185m	5	<1	0	<1
Manganese p	opm	ASTM D5185m		<1	0	0
Magnesium p	opm	ASTM D5185m	25	0	<1	<1
Calcium p	opm	ASTM D5185m	200	0	2	0
Phosphorus p	opm	ASTM D5185m	300	372	384	420
Zinc p	opm	ASTM D5185m	370	9	<1	0
Sulfur p	opm	ASTM D5185m	2500	445	433	442
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon p	opm	ASTM D5185m	>15	2	2	2
		ASTM D5185m		0	<1	0
	opm	ASTM D5185m		2	<1	2
FLUID CLEANLIN	VESS	method	limit/base	current	history1	history2
Particles >4µm	.200	ASTM D7647	>10000	▲ 66566	▲ 94854	▲ 108950
Particles >6µm		ASTM D7647 ASTM D7647	>2500	▲ 17896	▲ 17657	▲ 19659
Particles >0µm		ASTM D7647 ASTM D7647	>2300	121	198	226
Particles >21µm		ASTM D7647 ASTM D7647	>160	9	28	31
Particles >38µm		ASTM D7647 ASTM D7647	>40	9	0	1
		ASTM D7647 ASTM D7647			0	0
Particles >71µm			>10	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/16	<b>23/21/14</b>	▲ 24/21/15	▲ 24/21/15
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ng KOH/g	ASTM D8045	0.57	0.17	0.16	0.17
47·09) Rev: 1	Submitted By: DAVID BOBINSON					


Report Id: KRAKIR [WUSCAR] 06213439 (Generated: 06/21/2024 11:47:09) Rev: 1

Submitted By: DAVID ROBINSON Page 1 of 2



# **OIL ANALYSIS REPORT**





Aug1/22 -

nr4/77

Dec25/22

Mav4/23


0ct5/23


60 Abnorma

50 May31/21

Vov7/21

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	68	65.5	65.77	66.2
SAMPLE IMAG	ES	method	limit/base	current	history1	history2
Color				PCANTUM	•	•
Bottom				Spice		





Report Id: KRAKIR [WUSCAR] 06213439 (Generated: 06/21/2024 11:47:09) Rev: 1

Submitted By: DAVID ROBINSON