

### **OIL ANALYSIS REPORT**

Sample Rating Trend



# Blue Bird 4849

#### Component Diesel Engine

Fluid PETRO CANADA DURON SHP 10W30 (18 QTS)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


#### Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0091578		
Sample Date		Client Info		23 Feb 2024		
Machine Age	mls	Client Info		45725		
Oil Age	mls	Client Info		45725		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>3.0	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	175		
Chromium	ppm	ASTM D5185m	>20	2		
Nickel	ppm	ASTM D5185m	>2	<1		
Titanium	ppm	ASTM D5185m	>2	<1		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>20	5		
Lead	ppm	ASTM D5185m	>40	1		
Copper	ppm	ASTM D5185m	>330	18		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 3	history1	history2
	ppm ppm					history2 
Boron		ASTM D5185m	2	3		
Boron Barium	ppm	ASTM D5185m ASTM D5185m	2 0	3 <1		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50	3 <1 62		
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0	3 <1 62 2		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950	3 <1 62 2 974		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950 1050	3 <1 62 2 974 1164		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995	3 <1 62 2 974 1164 1026		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180	3 <1 62 2 974 1164 1026 1296		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600	3 <1 62 2 974 1164 1026 1296 3145		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600	3 <1 62 2 974 1164 1026 1296 3145 current		    history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m <b>method</b> ASTM D5185m	2 0 50 950 1050 995 1180 2600	3 <1 62 2 974 1164 1026 1296 3145 current 9	     history1	    history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m <b>method</b> ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600 limit/base >25	3 <1 62 2 974 1164 1026 1296 3145 current 9 4	     history1	     history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600 <b>limit/base</b> >25	3 <1 62 2 974 1164 1026 1296 3145 current 9 4 6	     history1  	    history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <b>limit/base</b> >25 -20 <b>limit/base</b>	3 <1 62 2 974 1164 1026 1296 3145 current 9 4 6 Current	    history1   history1	     history2   history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <b>limit/base</b> >25 >20 <b>limit/base</b>	3 <1 62 2 974 1164 1026 1296 3145 <i>current</i> 9 4 6 <i>current</i> 2	     history1   history1 	    history2  history2  history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 0 950 1050 995 1180 2600 <i>limit/base</i> >25 20 <i>limit/base</i> >20	3 <1 62 2 974 1164 1026 1296 3145 <i>current</i> 9 4 6 <i>current</i> 2 15.3	     history1   history1  	     history2   history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	2 0 50 950 1050 995 1180 2600 <b>imit/base</b> >25 20 <b>imit/base</b> >6 >20	3 <1 62 2 974 1164 1026 1296 3145 <b>current</b> 9 4 6 <b>current</b> 2 15.3 28.9	      history1  history1  history1	    history2  history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844 *ASTM D7624 *ASTM D7415	2 0 50 0 950 1050 995 1180 2600 <b>imit/base</b> >25 20 <b>imit/base</b> >6 >20 >30	3 <1 62 2 974 1164 1026 1296 3145 <i>current</i> 9 4 6 <i>current</i> 2 15.3 28.9 <i>current</i>	     history1  history1  history1  history1	     history2  history2  history2  history2



## **OIL ANALYSIS REPORT**





VIS	SUAL	metho	od limit/ba	se current	history1	history2
White	Metal sc	alar *Visual	NONE	NONE		
Yellow	v Metal sc	alar *Visual	NONE	NONE		
Precip		alar *Visual		NONE		
Silt		alar *Visual	NONE	NONE		
Debris		alar *Visual		NONE		
Sand/		alar *Visual		NONE		
-		alar *Visual				
Appea Odor		alar *Visual				
		alar *Visual		NEG		
Free \	Nater sc	alar *Visual		NEG		
FLU	JID PROPERT			se current	history1	history2
			445 12.00	11.6		
GR	APHS					
Ferr	ous Alloys					
	iron					
140 - 140 -	nickel					
120-						
E <sup>100</sup>						
60						
40 -						
20						
Feb 23/24			Feb 23/24			
	<i>c</i> <b>b b b b</b>		8			
	-ferrous Metals					
	copper					
14-	****** lead					
12						
E 10						
6						
4						
2						
0		******	24			
Feb 23/24			Feb23/24			
	osity @ 100°C		ц	Dees No. 1	aar	
15				Base Numl		
14 - Abnor	imai			5.0		
13-				¥0.4.0		
(50 12 Base 001) tg 11-		****		Bm)		
tz 11				(B)H 4.0 - 3.0 - 3.0 - 2.0 -		
10				2.0		
9- Abno	rmai			<sup>66</sup> 1.0		
8				0.0		
Feb23/24			Feb23/24 -	Feb23/24		Feb23/24
Feb2			Feb2	Feb2		Feb 2
boratory : WearC	heck USA - 501 Ma	adison Ave	Carv NC 275	13	ICSR	588 - Kankakee
ample No. : PCA00		Received	: 20 Jun 202			dustrial Parkway
ab Number : 062153		ested	: 21 Jun 202	4		Kankakee, IL
ique Number : 110881	98 <b>C</b>	)iagnosed	: 21 Jun 2024	- Sean Felton		US 60901
est Package : FLEET	Suctomor Sonvice	+ 1 000 007	1260			act: Zoltan Sziky

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Submitted By: Chad Ingold

T: (815)295-8231

z.sziky@illinois-central.com

Page 2 of 2

F: