


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Area  
**(51482Z) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A63348**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0121343</b>	PCA0106577	PCA0094994
Sample Date	Client Info		<b>04 Jun 2024</b>	23 Feb 2024	14 Jul 2023
Machine Age	mls	Client Info	<b>178747</b>	147751	87272
Oil Age	mls	Client Info	<b>30000</b>	60000	40422
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

### CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

### WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	<b>25</b>	41	38
Chromium	ppm	ASTM D5185m >5	<b>2</b>	4	4
Nickel	ppm	ASTM D5185m >2	<b>&lt;1</b>	1	<1
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>&lt;1</b>	<1	0
Aluminum	ppm	ASTM D5185m >30	<b>12</b>	25	45
Lead	ppm	ASTM D5185m >30	<b>0</b>	0	1
Copper	ppm	ASTM D5185m >150	<b>30</b>	58	120
Tin	ppm	ASTM D5185m >5	<b>&lt;1</b>	1	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

### ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>3</b>	2	3
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>59</b>	57	56
Manganese	ppm	ASTM D5185m 0	<b>1</b>	2	2
Magnesium	ppm	ASTM D5185m 950	<b>955</b>	931	880
Calcium	ppm	ASTM D5185m 1050	<b>1142</b>	1138	1321
Phosphorus	ppm	ASTM D5185m 995	<b>963</b>	929	849
Zinc	ppm	ASTM D5185m 1180	<b>1254</b>	1219	1112
Sulfur	ppm	ASTM D5185m 2600	<b>3024</b>	2146	2339

### CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	<b>6</b>	6	6
Sodium	ppm	ASTM D5185m	<b>4</b>	2	4
Potassium	ppm	ASTM D5185m >20	<b>21</b>	48	95




### INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.7</b>	1.1	0.7
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.6</b>	11.0	9.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.8</b>	22.8	22.1

### FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.8</b>	20.8	19.6
Base Number (BN)	mg KOH/g	ASTM D2896	<b>6.3</b>	5.5	6.7





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.7	11.5

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0121343      **Received** : 20 Jun 2024  
**Lab Number** : **06215436**      **Tested** : 21 Jun 2024  
**Unique Number** : 11088300      **Diagnosed** : 21 Jun 2024 - Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1369 - Berkeley-Waxahachie**  
 710 Ovilla Road  
 Waxahachie, TX  
 US 75167

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)