

# **OIL ANALYSIS REPORT**

#### DODT

### NORMAL


Area

# (69964Z) Walgreens - Tractor [Walgreens - Tractor] 136A624261

**Diesel Engine** 

Fluid

PETRO CANADA DURON SHP 10W30 (11 GAL





#### DIAGNOSIS

#### Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

#### Wear

Metal levels are typical for a new component breaking in.

#### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.


#### **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

GAL)				Jun2024		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0121349		
Sample Date		Client Info		10 Jun 2024		
Machine Age	mls	Client Info		60044		
Oil Age	mls	Client Info		60044		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	76		
Chromium	ppm	ASTM D5185m	>5	7		
Nickel	ppm	ASTM D5185m	>2	2		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	<1		
Aluminum	ppm	ASTM D5185m	>30	102		
Lead	ppm	ASTM D5185m	>30	<1		
Copper	ppm	ASTM D5185m	>150	190		
Tin	ppm	ASTM D5185m	>5	7		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	27		
Barium	ppm	ASTM D5185m	0	<1		
Molybdenum	ppm	ASTM D5185m	50	44		
Manganese	ppm	ASTM D5185m	0	6		
Magnesium	ppm	ASTM D5185m	950	535		
Calcium	ppm	ASTM D5185m	1050	1831		
Phosphorus	ppm	ASTM D5185m	995	812		
Zinc	ppm	ASTM D5185m	1180	935		
Sulfur	ppm	ASTM D5185m	2600	2080		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	10		
Sodium	ppm	ASTM D5185m		5		
Potassium	ppm	ASTM D5185m	>20	247		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.5		
Nitration	Abs/cm	*ASTM D7624	>20	12.0		
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.7		
FLUID DEGRA	OATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	27.3		
Base Number (BN)	mg KOH/g	ASTM D2896		5.6		
()	0 - 0					



## **OIL ANALYSIS REPORT**





Certificate 12367

Laboratory Sample No. Lab Number

: 06215444

: PCA0121349 Unique Number : 11088308 Test Package : FLEET

Received **Tested** 

Diagnosed

: 20 Jun 2024 : 21 Jun 2024 : 21 Jun 2024 - Don Baldridge

710 Ovilla Road Waxahachie, TX US 75167

Contact: Robert Beal rbeal@transervice.com T: (972)923-9928

To discuss this sample report, contact Customer Service at 1-800-237-1369.  $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (972)923-9919