




# OIL ANALYSIS REPORT

## Sample Rating Trend



GLYCOL



Machine Id

**821081**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Check for low coolant level. We advise that you check for the source of the coolant leak. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

### Wear

Blower/turbocharger and/or piston wear is indicated.

### Contamination

Sodium and/or potassium levels are high.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0118474</b>	GFL0118481	GFL0118495
Sample Date	Client Info	<b>12 Jun 2024</b>	04 Jun 2024	15 Apr 2024
Machine Age	hrs	<b>8403</b>	0	0
Oil Age	hrs	<b>650</b>	0	0
Oil Changed	Client Info	<b>Changed</b>	Not Changd	Not Changd
Sample Status		<b>ABNORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>50</b>	19	68
Chromium	ppm ASTM D5185m >20	<b>2</b>	<1	2
Nickel	ppm ASTM D5185m >4	<b>0</b>	<1	0
Titanium	ppm ASTM D5185m	<b>0</b>	<1	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>▲ 46</b>	4	49
Lead	ppm ASTM D5185m >40	<b>0</b>	<1	<1
Copper	ppm ASTM D5185m >330	<b>&lt;1</b>	7	2
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>4</b>	1	2
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>68</b>	69	88
Manganese	ppm ASTM D5185m 0	<b>1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>977</b>	916	1366
Calcium	ppm ASTM D5185m 1070	<b>1101</b>	1111	1572
Phosphorus	ppm ASTM D5185m 1150	<b>1131</b>	1056	1658
Zinc	ppm ASTM D5185m 1270	<b>1312</b>	1212	1859
Sulfur	ppm ASTM D5185m 2060	<b>3604</b>	3105	4426

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>10</b>	7	11
Sodium	ppm ASTM D5185m	<b>● 97</b>	33	5
Potassium	ppm ASTM D5185m >20	<b>▲ 141</b>	33	76
Glycol	% *ASTM D2982	<b>NEG</b>	NEG	NEG

## INFRA-RED






method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>1.3</b>	0.4	1.2
Nitration	Abs/cm *ASTM D7624 >20	<b>8.9</b>	7.4	8.9
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.7</b>	19.2	20.8

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>14.6</b>	14.6	15.1
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>9.3</b>	8.6	8.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.9</b>	13.9	13.8

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0118474      **Received** : 21 Jun 2024  
**Lab Number** : **06216687**      **Tested** : 24 Jun 2024  
**Unique Number** : 11089551      **Diagnosed** : 24 Jun 2024 - Sean Felton  
**Test Package** : FLEET ( Additional Tests: Glycol )

**GFL Environmental - 893 - OK East Hauling**  
 2100 Lilly Street  
 Seminole, OK  
 US 74868

Contact: Roger Barlow  
 rbarlow@gflenv.com  
 T: (405)204-6183

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)