Sample Rating Trend



PROBLEM SUMMARY



Machine Id WL0128 Component Diesel Engine Fluid PETRO CANADA DURON SHP 15W40 (--- GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

PROBLEMATIC TEST RESULTS								
Sample Status				SEVERE				
Silicon	ppm	ASTM D5185m	>25	113				
	ppm	/ lo lill Bolloolli	220					

Customer Id: GFL821 Sample No.: GFL0121617 Lab Number: 06219299 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data: Don Baldridge +1 <u>don.b505@comcast.net</u>

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

RECOMMENDED ACTIONS						
Action	Status	Date	Done By	Description		
Change Fluid			?	We recommend that you drain the oil from the component if this has not already been done.		
Resample			?	We recommend an early resample to monitor this condition.		
Check Dirt Access			?	We advise that you check the air filter, air induction system, and any areas where dirt may enter the component.		

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT



Machine Id

WL0128 Component Diesel Engine Fluid PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Elemental level of silicon (Si) above normal.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0121617		
Sample Date		Client Info		20 Jun 2024		
Machine Age	hrs	Client Info		21823		
Oil Age	hrs	Client Info		300		
Oil Changed		Client Info		Not Changd		
Sample Status				SEVERE		
CONTAMINATI	ON	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	37		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>4	1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	<1		
Aluminum	ppm	ASTM D5185m	>20	3		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	10		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	nnm	ASTM D5185m		.4		
	ppm	AO INI DO IODIII		<1		
ADDITIVES	ppm	method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current	history1	history2
ADDITIVES Boron Barium	ppm ppm	method ASTM D5185m ASTM D5185m	limit/base 0 0	current 23 2	history1 	history2
ADDITIVES Boron Barium Molybdenum	ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 60	 current 23 2 66 	 history1 	history2
ADDITIVES Boron Barium Molybdenum Manganese	ppm ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 60 0	< 1 current 23 2 66 1	 history1 	 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 60 0 0 1010	< r current 23 2 66 1 557	 history1 	 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 60 0 1010 1070	< r current 23 2 66 1 557 1657	 history1 	 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm ppm	Method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 60 0 1010 1070 1150	 current 23 2 66 1 557 1657 1120 	 history1 	 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm ppm	ACTM D5185mASTM D5185mASTM D5185mASTM D5185mASTM D5185mASTM D5185mASTM D5185mASTM D5185mASTM D5185mASTM D5185m	limit/base 0 0 60 0 1010 1070 1150 1270	 current 23 2 66 1 557 1657 1120 1341 	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	ACTM D5185mASTM D5185m	limit/base 0 0 60 0 1010 1070 1150 1270 2060	 current 23 2 66 1 557 1657 1120 1341 3335 	history1	 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ACTM DS105000ASTM D518500ASTM D518500	limit/base 0 0 60 0 1010 1070 1150 1150 1270 2060	<1 current 23 2 66 1 557 1657 1120 1341 3335 current	history1	history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 60 0 1010 1070 1150 1150 1270 2060 limit/base >25	<1 current 23 2 66 1 557 1657 1120 1341 3335 current ▲ 113	history1	history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base 0 0 0 1010 1070 1150 1270 2060 limit/base >25	<1 current 23 2 66 1 557 1657 1120 1341 3335 current ▲ 113 1	history1	history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	North Doftsom method ASTM D5185m	limit/base 0 0 0 0 1010 1070 1150 11270 2060 limit/base >25	<1 current 23 2 66 1 557 1657 1120 1341 3335 current ▲ 113 1 2	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm	ASTM DS185m ASTM D5185m	limit/base 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	<1 current 23 2 66 1 557 1657 1120 1341 3335 current ▲ 113 1 2 current	history1	history2 history2 history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	limit/base 0 0 0 1010 1010 1070 1150 1270 2060 limit/base >25 limit/base >3	<1 current 23 2 66 1 557 1657 1120 1341 3335 current ▲ 113 1 2 current 0.4	history1	history2 history2 history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	limit/base 0 0 60 0 1010 1070 1270 2060 limit/base >25 limit/base >20 >20	<t Current 23 2 66 1 557 1657 1120 1341 3335 Current ▲ 113 1 2 Current 0.4 9.9 </t 	history1 history1 history1 history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm TS ppm ppm ppm	ACTIM DS1050000 ASTM D5185000 ASTM D78444 *ASTM D7624 *ASTM D7415000000000000000000000000000000000000	limit/base 0 0 0 1010 1070 1150 1150 2060 limit/base >25 limit/base >20 limit/base >3 >20	<1 current 23 2 66 1 557 1657 1657 1120 1341 3335 current ▲ 113 1 2 current 0.4 9.9 22.5	history1 history1 history1 history1 history1 history1 <	history2 history2 history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRAL	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	limit/base 0 0 0 0 0 1010 1070 1270 2060 limit/base >20 limit/base >3 >20 >30 limit/base	<t 0.4="" 1="" 1120="" 113="" 1341="" 1657="" 2="" 22.5="" 23="" 3335="" 557="" 66="" 9.9="" current="" current<="" th="" ▲=""><th>history1 history1 history1 history1 history1 history1 history1</th><th>history2 history2 history2 history2 history2 history2 history2 history2 history2 history2 history2 history2</th></t>	history1 history1 history1 history1 history1 history1 history1	history2 history2 history2 history2 history2 history2 history2 history2 history2 history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRAD Oxidation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m ASTM D7844 *ASTM D7844 *ASTM D7415 method *ASTM D7414	limit/base 0 0 0 0 1010 1070 1150 1270 2060 limit/base >20 limit/base >3 >20 >30 limit/base >25	<1 current 23 2 66 1 557 1657 1120 1341 3335 current ▲ 113 1 2 current 0.4 9.9 22.5 current 18.8	history1	history2 history2 history2 history2 history2 history2 history2 history2 history2 history2 history2 history2



bpm

(mg KOH/g)

Imber

Base

OIL ANALYSIS REPORT



To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Submitted By: Gary Southard

landen.johnson@gflenv.com

Page 4 of 4

E:

Lebanon, MO

T: (417)664-0010

US 65536