


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**2026854**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON UHP 5W30 (--- QTS)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0128352</b>	PCA0119526	PCA0114136
Sample Date	Client Info			<b>11 Jun 2024</b>	21 Mar 2024	09 Dec 2023
Machine Age	mls Client Info			<b>266251</b>	0	227652
Oil Age	mls Client Info			<b>19993</b>	0	0
Oil Changed	Client Info			<b>Not Changed</b>	Changed	Not Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>18</b>	48	29
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	1	<1
Nickel	ppm	ASTM D5185m	>4	<b>1</b>	2	<1
Titanium	ppm	ASTM D5185m		<b>35</b>	8	2
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>20	<b>3</b>	6	4
Lead	ppm	ASTM D5185m	>40	<b>0</b>	1	1
Copper	ppm	ASTM D5185m	>330	<b>5</b>	10	8
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	<1




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	<b>19</b>	5	0
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	64	<b>36</b>	57	61
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	1	<1
Magnesium	ppm	ASTM D5185m	1160	<b>776</b>	953	927
Calcium	ppm	ASTM D5185m	820	<b>1421</b>	1236	1107
Phosphorus	ppm	ASTM D5185m	1160	<b>1094</b>	1031	938
Zinc	ppm	ASTM D5185m	1260	<b>1299</b>	1313	1219
Sulfur	ppm	ASTM D5185m	3000	<b>4156</b>	3546	3265

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>5</b>	6	5
Sodium	ppm	ASTM D5185m		<b>2</b>	4	2
Potassium	ppm	ASTM D5185m	>20	<b>4</b>	9	9

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.4</b>	0.8	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.3</b>	12.7	10.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.6</b>	25.2	23.3

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.5</b>	21.0	19.1
Base Number (BN)	mg KOH/g	ASTM D2896	11.0	<b>5.1</b>	5.2	4.8





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	11.9	11.1	11.1

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0128352      **Received** : 25 Jun 2024  
**Lab Number** : 06219412      **Tested** : 25 Jun 2024  
**Unique Number** : 11097609      **Diagnosed** : 25 Jun 2024 - Wes Davis  
**Test Package** : FLEET

**PERDUE FARMS - GEORGETOWN**  
 20621 SAVANAH RD  
 GEORGETOWN, DE  
 US 19947  
 Contact: ROBERT LOCKWOOD  
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)