


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
2026857
 Component
Front Differential
 Fluid
PETRO CANADA TRAXON 75W90 SYNTHETIC (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0121384	PCA0113252	PCA0104339
Sample Date	Client Info		02 Apr 2024	27 Nov 2023	24 Aug 2023
Machine Age	mls	Client Info	269629	0	232826
Oil Age	mls	Client Info	269629	251046	232826
Oil Changed	Client Info		Not Chngd	Not Chngd	Not Chngd
Sample Status			NORMAL	NORMAL	ABNORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>.2	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >500	457	378	169
Chromium	ppm	ASTM D5185m >10	3	3	2
Nickel	ppm	ASTM D5185m >10	7	6	8
Titanium	ppm	ASTM D5185m	<1	<1	0
Silver	ppm	ASTM D5185m	0	0	0
Aluminum	ppm	ASTM D5185m >25	3	1	3
Lead	ppm	ASTM D5185m >25	3	2	0
Copper	ppm	ASTM D5185m >100	63	56	4
Tin	ppm	ASTM D5185m >10	3	2	0
Vanadium	ppm	ASTM D5185m	0	<1	<1
Cadmium	ppm	ASTM D5185m	0	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 328	231	232	266
Barium	ppm	ASTM D5185m 1	2	0	0
Molybdenum	ppm	ASTM D5185m	0	<1	0
Manganese	ppm	ASTM D5185m	15	14	12
Magnesium	ppm	ASTM D5185m 1	2	1	0
Calcium	ppm	ASTM D5185m 7	0	12	0
Phosphorus	ppm	ASTM D5185m 1145	1634	1320	1352
Zinc	ppm	ASTM D5185m 3	23	0	0
Sulfur	ppm	ASTM D5185m 17909	25085	23137	24355


CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >75	58	55	36
Sodium	ppm	ASTM D5185m	12	8	6
Potassium	ppm	ASTM D5185m >20	5	3	0

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual NONE	NONE	NONE	NONE
Silt	scalar	*Visual NONE	NONE	NONE	NONE
Debris	scalar	*Visual NONE	NONE	NONE	▲ MODER
Sand/Dirt	scalar	*Visual NONE	NONE	NONE	NONE
Appearance	scalar	*Visual NORML	NORML	NORML	NORML
Odor	scalar	*Visual NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual >.2	NEG	NEG	NEG
Free Water	scalar	*Visual	NEG	NEG	NEG

OIL ANALYSIS REPORT






FLUID PROPERTIES

	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	99.6	101	102

SAMPLE IMAGES

	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0121384
Lab Number : **06220143**
Unique Number : 11098340
Test Package : FLEET
Received : 25 Jun 2024
Tested : 26 Jun 2024
Diagnosed : 26 Jun 2024 - Wes Davis

PERDUE FARMS - GEORGETOWN
 20621 SAVANAH RD
 GEORGETOWN, DE
 US 19947
 Contact: ROBERT LOCKWOOD
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)