


OIL ANALYSIS REPORT

Sample Rating Trend







Machine Id 733022

Component Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 668 (-

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.


668 (GAL)			Feb 2024	Jun 2024		
SAMPLE INFOF	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0121740	GFL0092165	
Sample Date		Client Info		20 Jun 2024	02 Feb 2024	
Machine Age	hrs	Client Info		3668	2469	
Oil Age	hrs	Client Info		1200	5621	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINAT	ΓΙΟΝ	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METAL	_S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>230	9	53	
Chromium	ppm	ASTM D5185m	>2	0	<1	
Nickel	ppm	ASTM D5185m	>5	0	2	
Titanium	ppm	ASTM D5185m	>2	0	<1	
Silver	ppm	ASTM D5185m	>5	0	<1	
Aluminum	ppm	ASTM D5185m	>65	6	21	
Lead	ppm	ASTM D5185m	>55	2	24	
Copper	ppm	ASTM D5185m	>85	3	10	
Tin	ppm	ASTM D5185m	>5	<1	4	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	<1	
ADDITIVES	PP	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	mmadaoo	68	111	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	2	
Manganese	ppm	ASTM D5185m		<1	2	
Magnesium	ppm	ASTM D5185m		11	3	
Calcium	ppm	ASTM D5185m		135	112	
Phosphorus	ppm	ASTM D5185m		240	280	
Zinc	ppm	ASTM D5185m		22	31	
Sulfur	ppm	ASTM D5185m		1943	1117	
CONTAMINAN	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	2	5	
Sodium	ppm	ASTM D5185m		3	0	
Potassium	ppm	ASTM D5185m	>20	2	5	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
00.00\ D4						





OIL ANALYSIS REPORT



FLUID PROF	ERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	34	33.1	35.1	
SAMPLE IMA	AGES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image









Certificate 12367

Laboratory

Sample No. : GFL0121740 Lab Number : 06221714 Unique Number : 11099911

Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received : 26 Jun 2024 Tested : 27 Jun 2024

: 27 Jun 2024 - Wes Davis Diagnosed

GFL Environmental - 856 - Houston South 8515 Highway 6 South

Houston, TX US 77083

Contact: Apolinar Zacarias pzacariascano@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: