


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL


Machine Id
631681
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (--- GAL)

DIAGNOSIS
Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0125181	PCA0119009	---
Sample Date	Client Info			08 Jun 2024	23 Feb 2024	---
Machine Age	mls Client Info			58617	49068	---
Oil Age	mls Client Info			58617	49068	---
Oil Changed	Client Info			Not Chngd	Changed	---
Sample Status				NORMAL	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	---
Water	WC Method	>0.2		NEG	NEG	---
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	30	74	---
Chromium	ppm	ASTM D5185m	>20	3	6	---
Nickel	ppm	ASTM D5185m	>4	<1	1	---
Titanium	ppm	ASTM D5185m		12	2	---
Silver	ppm	ASTM D5185m	>3	<1	<1	---
Aluminum	ppm	ASTM D5185m	>20	35	98	---
Lead	ppm	ASTM D5185m	>40	<1	0	---
Copper	ppm	ASTM D5185m	>330	90	284	---
Tin	ppm	ASTM D5185m	>15	2	6	---
Vanadium	ppm	ASTM D5185m		<1	<1	---
Cadmium	ppm	ASTM D5185m		0	0	---




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	25	21	---
Barium	ppm	ASTM D5185m	0	0	<1	---
Molybdenum	ppm	ASTM D5185m	50	47	43	---
Manganese	ppm	ASTM D5185m	0	2	5	---
Magnesium	ppm	ASTM D5185m	950	797	584	---
Calcium	ppm	ASTM D5185m	1050	1358	1668	---
Phosphorus	ppm	ASTM D5185m	995	1022	840	---
Zinc	ppm	ASTM D5185m	1180	1233	1002	---
Sulfur	ppm	ASTM D5185m	2600	3312	1990	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5	8	---
Sodium	ppm	ASTM D5185m		7	7	---
Potassium	ppm	ASTM D5185m	>20	91	274	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.6	1.3	---
Nitration	Abs/cm	*ASTM D7624	>20	8.3	12.8	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	20.4	25.5	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.7	28.6	---
Base Number (BN)	mg KOH/g	ASTM D2896		8.1	5.5	---









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.0	10.4

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0125181 **Received** : 27 Jun 2024
Lab Number : 06222046 **Tested** : 27 Jun 2024
Unique Number : 11100243 **Diagnosed** : 27 Jun 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #118
 2196 BENNETT ROAD
 PHILADELPHIA, PA
 US 19116

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Contact: ROSTY VITER
rviter@millertransgroup.com

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (215)552-9832

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (215)552-9892