

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 834010 Component Natural Gas Engine Fluid {not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

Metal levels are typical for a components first oil change.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0122006		
Sample Date		Client Info		25 Jun 2024		
Machine Age	hrs	Client Info		533		
Oil Age	hrs	Client Info		533		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS	S .	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	49		
Chromium	ppm	ASTM D5185m	>4	<1		
Nickel	ppm	ASTM D5185m	>2	1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	<1		
Aluminum	ppm	ASTM D5185m	>9	6		
Lead	ppm	ASTM D5185m	>30	2		
Copper	ppm	ASTM D5185m	>35	20		
Tin	ppm	ASTM D5185m	>4	1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		13		
Barium	ppm	ASTM D5185m		4		
Molybdenum	ppm	ASTM D5185m		54		
Manganese	ppm	ASTM D5185m		15		
Magnesium						
magnoolann	ppm	ASTM D5185m		825		
0	ppm ppm	ASTM D5185m ASTM D5185m		825 1239		
Calcium						
Calcium Phosphorus	ppm	ASTM D5185m		1239		
Calcium Phosphorus Zinc	ppm ppm	ASTM D5185m ASTM D5185m		1239 780		
Calcium Phosphorus Zinc	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	1239 780 1021		
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	limit/base >+100	1239 780 1021 2648		
Calcium Phosphorus Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method		1239 780 1021 2648 current	 history1	 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm TS ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m		1239 780 1021 2648 current 32	 history1	 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm TS ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>+100	1239 780 1021 2648 current 32 9	 history1 	 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm TS ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>+100 >20	1239 780 1021 2648 current 32 9 13	 history1 	 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>+100 >20 limit/base	1239 780 1021 2648 current 32 9 13 current	 history1 history1	 history2 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>+100 >20 limit/base	1239 780 1021 2648 current 32 9 13 current 0	 history1 history1 	 history2 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm TS ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7844 *ASTM D7844 *ASTM D7844	>+100 >20 limit/base	1239 780 1021 2648 <u>current</u> 32 9 13 <u>current</u> 0 12.2	 history1 history1 history1	 history2 history2
Calcium Phosphorus Zinc Sulfur CONTAMINAN Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm TS ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7844 *ASTM D7844 *ASTM D7844	>+100 >20 limit/base >20 >30 limit/base	1239 780 1021 2648 current 32 9 13 current 0 12.2 23.2	 history1 history1 history1 	 history2 history2



OIL ANALYSIS REPORT

σ¯¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬¬		VISUAL		method				history2
Oxidation		White Metal	scalar	*Visual	NONE	NONE		
suffation		Yellow Metal	scalar	*Visual	NONE	NONE		
- Abnormal		Precipitate	scalar	*Visual	NONE	NONE		
)-		Silt	scalar	*Visual	NONE	NONE		
		Debris	scalar	*Visual	NONE	NONE		
		Sand/Dirt	scalar	*Visual	NONE	NONE		
5/24 4	5/24	Appearance	scalar	*Visual	NORML	NORML		
Jun 25/24	Jun25/24	Odor	scalar	*Visual	NORML	NORML		
	-	Emulsified Water	scalar	*Visual	>0.1	NEG		
Base Number		Free Water	scalar	*Visual	2011	NEG		
		FLUID PROPI		method	limit/base	current	history1	history2
		Visc @ 100°C	cSt	ASTM D445		14.4		
)-		GRAPHS						
		Ferrous Alloys						
24	V C	50 iron						
Jun25/24	1.361	40 -						
Viscosity @ 100°C		30 -						
T:		E 20						
Abnormal								
		10-						
-								
		Jun25/24			Jun25/24			
Abnormal					Jur			
	V C	Non-ferrous Meta	als					
Jun 25/24	136-	copper						
<u>٦</u>	-	15						
		Ē_10-						
		5						
		24 24			24			
		Jun25/24			Jun25/24			
		Viscosity @ 100°	С		,	Base Number		
		16 Abnormal			4.5			
		15 - Abnormal			4.0			
		14			B 3.5 H 0 3.0			
		(2-001) 13- 753			(B3.5 DH 03 3.0 E 2.5			
		CSt (1						
		12			210			
		Abnormal			e 1.0			
		10			0.5			
		5/24				5/24		
		Jun25/24			Jun25/24	Jun25/24		
		: WearCheck USA - 5 : GFL0122006 : 06222164	01 Madiso Rece Teste	ved : 2	v, NC 27513 7 Jun 2024 3 Jun 2024	GFL Envir	ronmental - 652 - Frec 1095 Frec	lericksburg Hau 4 Houser Dr

Submitted By: TECHNICIAN ACCOUNT