


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
PREVOST 113

Component
Rear Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			PCA0125068	PCA0101050	PCA0094190
Sample Date	Client Info			10 May 2024	02 Nov 2023	06 Jul 2023
Machine Age	mls	Client Info		276274	256634	244014
Oil Age	mls	Client Info		8644	12620	10989
Oil Changed	Client Info			Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	12	14	12
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	1	1	2
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	12	18	11
Lead	ppm	ASTM D5185m	>40	<1	<1	<1
Copper	ppm	ASTM D5185m	>330	1	<1	1
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	<1	4	<1
Barium	ppm	ASTM D5185m	0	<1	0	2
Molybdenum	ppm	ASTM D5185m	60	54	58	63
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	873	942	955
Calcium	ppm	ASTM D5185m	1070	1012	996	1106
Phosphorus	ppm	ASTM D5185m	1150	966	946	1010
Zinc	ppm	ASTM D5185m	1270	1180	1243	1275
Sulfur	ppm	ASTM D5185m	2060	2995	2822	3313


CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3	3	3
Sodium	ppm	ASTM D5185m		5	6	5
Potassium	ppm	ASTM D5185m	>20	2	0	<1

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.4	0.6	0.5
Nitration	Abs/cm	*ASTM D7624	>20	7.2	7.7	7.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.9	19.5	19.9


FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.1	14.6	15.2
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	9.02	7.37	9.74

OIL ANALYSIS REPORT


FT-IR (Direct Trend)




Acid Number



Viscosity @ 100°C











Acid Number



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.1	14.0

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : PCA0125068

Lab Number : 06222496

Unique Number : 11100693

Test Package : MOB 2 (Additional Tests: TAN Man)

Received : 27 Jun 2024

Tested : 28 Jun 2024

Diagnosed : 28 Jun 2024 - Angela Borella

BROWN BUS COMPANY - UPSTATE TRANSIT

50 VENNERS ROAD

AMSTERDAM, NY

US 12010

Contact: CONNIE WILBUR

cwilbur@browncoach.com

T: (518)843-4700

F: (518)843-3600

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)