




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(46510R) {UNASSIGNED}

Machine Id
729102

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0119876	GFL0103545	GFL0103587
Sample Date	Client Info	24 Jun 2024	27 Feb 2024	13 Dec 2023
Machine Age	hrs Client Info	0	0	0
Oil Age	hrs Client Info	480	540	595
Oil Changed	Client Info	N/A	Changed	N/A
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	39	17	7
Chromium	ppm ASTM D5185m >5	1	<1	<1
Nickel	ppm ASTM D5185m >4	1	0	0
Titanium	ppm ASTM D5185m >2	0	0	0
Silver	ppm ASTM D5185m >2	<1	0	0
Aluminum	ppm ASTM D5185m >15	4	4	3
Lead	ppm ASTM D5185m >25	0	0	<1
Copper	ppm ASTM D5185m >100	3	2	1
Tin	ppm ASTM D5185m >4	0	0	0
Vanadium	ppm ASTM D5185m	<1	<1	<1
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	4	<1	<1
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 60	64	63	60
Manganese	ppm ASTM D5185m 0	1	<1	0
Magnesium	ppm ASTM D5185m 1010	1067	959	980
Calcium	ppm ASTM D5185m 1070	1163	1087	1017
Phosphorus	ppm ASTM D5185m 1150	1129	976	1016
Zinc	ppm ASTM D5185m 1270	1419	1208	1284
Sulfur	ppm ASTM D5185m 2060	3804	3009	3176

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	7	4	2
Sodium	ppm ASTM D5185m	45	2	<1
Potassium	ppm ASTM D5185m >20	4	<1	<1

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	1.2	0.8	0.6
Nitration	Abs/cm *ASTM D7624 >20	10.2	7.7	6.3
Sulfation	Abs/.1mm *ASTM D7415 >30	23.5	19.6	19.2

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	19.5	14.7	14.3
Base Number (BN)	mg KOH/g ASTM D2896 9.8	7.7	8.6	8.9







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.9	13.8

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0119876
Lab Number : 06222997
Unique Number : 11101194
Test Package : FLEET
Received : 27 Jun 2024
Tested : 28 Jun 2024
Diagnosed : 28 Jun 2024 - Wes Davis

GFL Environmental - 958 - Tri County HC Morton
 1090 W. Jefferson St.
 Morton, IL
 US 61550
 Contact: Bryan Link
 blink@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)