




# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id  
**729089-13135**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1    | history2    |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info |             | <b>GFL0103530</b>  | GFL0103576  | GFL0103551  |
| Sample Date   | Client Info |             | <b>25 Jun 2024</b> | 12 Jun 2024 | 06 Mar 2024 |
| Machine Age   | hrs         | Client Info | <b>7846</b>        | 7758        | 7118        |
| Oil Age       | hrs         | Client Info | <b>0</b>           | 7758        | 0           |
| Oil Changed   | Client Info |             | <b>Not Changed</b> | Changed     | Changed     |
| Sample Status |             |             | <b>NORMAL</b>      | NORMAL      | NORMAL      |

## CONTAMINATION

|        | method    | limit/base | current        | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel   | WC Method | >5         | <b>&lt;1.0</b> | <1.0     | <1.0     |
| Water  | WC Method | >0.2       | <b>NEG</b>     | NEG      | NEG      |
| Glycol | WC Method |            | <b>NEG</b>     | NEG      | NEG      |

## WEAR METALS

|          | method | limit/base       | current      | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron     | ppm    | ASTM D5185m >80  | <b>13</b>    | 71       | 24       |
| Chromium | ppm    | ASTM D5185m >5   | <b>&lt;1</b> | 2        | <1       |
| Nickel   | ppm    | ASTM D5185m >2   | <b>0</b>     | <1       | 0        |
| Titanium | ppm    | ASTM D5185m      | <b>&lt;1</b> | <1       | 0        |
| Silver   | ppm    | ASTM D5185m >3   | <b>0</b>     | <1       | 0        |
| Aluminum | ppm    | ASTM D5185m >30  | <b>1</b>     | 4        | 1        |
| Lead     | ppm    | ASTM D5185m >30  | <b>0</b>     | 0        | 0        |
| Copper   | ppm    | ASTM D5185m >150 | <b>&lt;1</b> | 2        | 1        |
| Tin      | ppm    | ASTM D5185m >5   | <b>0</b>     | <1       | 0        |
| Vanadium | ppm    | ASTM D5185m      | <b>&lt;1</b> | 0        | 0        |
| Cadmium  | ppm    | ASTM D5185m      | <b>0</b>     | 0        | 0        |

## ADDITIVES

|            | method | limit/base       | current      | history1 | history2 |
|------------|--------|------------------|--------------|----------|----------|
| Boron      | ppm    | ASTM D5185m 0    | <b>&lt;1</b> | 3        | <1       |
| Barium     | ppm    | ASTM D5185m 0    | <b>0</b>     | 0        | 0        |
| Molybdenum | ppm    | ASTM D5185m 60   | <b>61</b>    | 65       | 61       |
| Manganese  | ppm    | ASTM D5185m 0    | <b>&lt;1</b> | 1        | 0        |
| Magnesium  | ppm    | ASTM D5185m 1010 | <b>1081</b>  | 1051     | 1056     |
| Calcium    | ppm    | ASTM D5185m 1070 | <b>1192</b>  | 1158     | 1143     |
| Phosphorus | ppm    | ASTM D5185m 1150 | <b>1149</b>  | 1139     | 1086     |
| Zinc       | ppm    | ASTM D5185m 1270 | <b>1478</b>  | 1401     | 1334     |
| Sulfur     | ppm    | ASTM D5185m 2060 | <b>4045</b>  | 3272     | 3579     |

## CONTAMINANTS

|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >20 | <b>4</b> | 15       | 9        |
| Sodium    | ppm    | ASTM D5185m     | <b>3</b> | 9        | 5        |
| Potassium | ppm    | ASTM D5185m >20 | <b>1</b> | 4        | 1        |

## INFRA-RED




|           | method   | limit/base      | current     | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot %    | %        | *ASTM D7844 >3  | <b>0.3</b>  | 1.1      | 0.6      |
| Nitration | Abs/cm   | *ASTM D7624 >20 | <b>6.7</b>  | 13.3     | 9.6      |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | <b>19.8</b> | 28.6     | 20.4     |

## FLUID DEGRADATION

|                  | method   | limit/base      | current     | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm | *ASTM D7414 >25 | <b>16.5</b> | 32.2     | 18.4     |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8  | <b>8.5</b>  | 4.6      | 8.0      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Yellow Metal     | scalar | *Visual    | NONE    | NONE     | NONE     |
| Precipitate      | scalar | *Visual    | NONE    | NONE     | NONE     |
| Silt             | scalar | *Visual    | NONE    | NONE     | NONE     |
| Debris           | scalar | *Visual    | NONE    | NONE     | NONE     |
| Sand/Dirt        | scalar | *Visual    | NONE    | NONE     | NONE     |
| Appearance       | scalar | *Visual    | NORML   | NORML    | NORML    |
| Odor             | scalar | *Visual    | NORML   | NORML    | NORML    |
| Emulsified Water | scalar | *Visual    | >0.2    | NEG      | NEG      |
| Free Water       | scalar | *Visual    |         | NEG      | NEG      |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 100°C     | cSt    | ASTM D445  | 15.4    | 14.5     | 14.3     |

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0103530      **Received** : 28 Jun 2024  
**Lab Number** : 06223295      **Tested** : 01 Jul 2024  
**Unique Number** : 11101492      **Diagnosed** : 01 Jul 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 958A - Chillicothe Wigan**  
 19908 N. State Rd 29  
 Chillicothe, IL  
 US 61523  
 Contact: Bryan Link  
 blink@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)