

OIL ANALYSIS REPORT

Sample Rating Trend





Area KEMP QUARRIES / RIVER VALLEY BACKBONE Machine Id OHT124 Component Transmission

MOBIL MOBILTRANS HD 30 (--- GAL)

DIAGNOSIS Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination


There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
|------------------|--------|-------------|------------|-------------|-------------|---------------|
| Sample Number | | Client Info | | PCA0108483 | PCA0084799 | PCA0084850 |
| Sample Date | | Client Info | | 19 Jun 2024 | 30 Jan 2024 | 25 Oct 2023 |
| Machine Age | hrs | Client Info | | 31138 | 30229 | 30229 |
| Oil Age | hrs | Client Info | | 31138 | 900 | 600 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Sample Status | | | | NORMAL | ABNORMAL | ABNORMAL |
| CONTAMINAT | ION | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| WEAR METAL | S | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >200 | 8 | 45 | 33 |
| Chromium | ppm | ASTM D5185m | >10 | 0 | <1 | 0 |
| Nickel | ppm | ASTM D5185m | | 0 | 1 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | 1 | <1 |
| Silver | ppm | ASTM D5185m | | 4 | 17 | 13 |
| Aluminum | ppm | ASTM D5185m | >50 | 2 | 3 | 2 |
| Lead | ppm | ASTM D5185m | >50 | 2 | 4 | 7 |
| Copper | ppm | ASTM D5185m | | 92 | ▲ 505 | <u> </u> |
| Tin | ppm | ASTM D5185m | >10 | <1 | 2 | <1 |
| Vanadium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | <1 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 5 | 3 | 4 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | | 0 | 6 | 4 |
| Manganese | ppm | ASTM D5185m | | <1 | 2 | <1 |
| Magnesium | ppm | ASTM D5185m | | 0 | 19 | 17 |
| Calcium | ppm | ASTM D5185m | | 3410 | 2707 | 2485 |
| Phosphorus | ppm | ASTM D5185m | | 980 | 934 | 792 |
| Zinc | ppm | ASTM D5185m | | 1164 | 1066 | 982 |
| Sulfur | ppm | ASTM D5185m | | 4281 | 3445 | 3560 |
| CONTAMINAN | TS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >50 | 7 | 14 | 12 |
| Sodium | ppm | ASTM D5185m | | 0 | 0 | 3 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 1 | 0 |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | LIGHT |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG | NEG |
| 1:29:59) Rev: 1 | | | | | | Submitted By: |







| | FLUID PRC | PERTIES | method | limit/base | current | history1 | history2 |
|---|--|---------------|----------------------|---|---------------------------|---|--|
| | Visc @ 40°C | cSt | ASTM D445 | 100 | 85.5 | 90.1 | 90.3 |
| | SAMPLE IN | AGES | method | limit/base | current | history1 | history2 |
| | Color | | | | no image | no image | no image |
| Jan30/24 Jun19/24 | Bottom | | | <u>-</u> | no image | no image | no image |
| | GRAPHS | | | L | | | |
| | Iron (ppm) | | | 200 | Lead (ppm) | | |
| | 400 - Severe | | | 150 | Smiore | | |
| | 300 200 - Abnormal | | | 틆 100 | | | |
| | 200 - Abnormal | | | 50 | Abnormal | | |
| | 0 | + | | 0 | | | |
| | Sep 18/23 | 0ct25/23 | Jan 30/24 | Jun 19/24 | Sep 18/23 | 0ct25/23 | |
| | Aluminum (pp | om) | | | Chromium (p | | |
| | 80 Severe | | | 30 | Sminn | 1 | |
| | Abnormal | | | 20 톮 15 | | | |
| | 20 | | | 10 | Abrement | | |
| | 0 | | | 5 | | | |
| | Sep 18/23 | 0ct25/23 | Jan30/24 | Jun 19/24 | Sep18/23 | 0ct25/23 | - |
| | o Copper (ppm) | | 7 | ٦٢ | ∞ Silicon (ppm) | - | 5 |
| | 600 500 | | _ | 140 | Severe | | |
| | 400 - Severe | | | 100 F 80 | | | |
| | 특 300 200 Abnormal | | | | Abnormal | | |
| | 100- | | | 20 | - | | |
| | Sep18/23 | 0ct25/23 + | Jan30/24 - | Jun19/24 | Sep 18/23 | 0ct25/23 - | |
| | 。 Viscosity @ 40 | | Jan | Jun | [₽] Additives | 000 | |
| | 115 110 Abnormal | | | 3500 | I | 1 | _ |
| | 105 - | | | 3000 2500 | phosphore | IS | |
| | (0.00 (0.00 (0.00 (0.00 (0.00) (0 | | | 톱 2000 | | | |
| | 90 85 Abnormal | | | 1500 | | | |
| | 80 | (/23 + | 1/24 | | | (/23 + | |
| | Sep 18/23 | 0ct25/23 | Jan 30/24 | Jun19/24 | Sep 18/23 | 0ct25/23 | |
| Laboratory Sample No. Lab Number Unique Number Test Package | : 11102329 | Rece Teste | ived : 28 ed : 01 | r, NC 27513 3 Jun 2024 1 Jul 2024 Jul 2024 - W | - | | alley - Backbo 600 S Hwy 29 Huntington, A US 7294 Contac |
| liscuss this sample report Denotes test methods that ements of conformity to sp | are outside of the IS | SO 17025 sco | ope of accred | litation. | | <bone@rivervall< td=""><td>eyquarries.co ٦ F</td></bone@rivervall<> | eyquarries.co ٦ F |

Report Id: KEMHUN [WUSCAR] 06224132 (Generated: 07/01/2024 11:29:59) Rev: 1