




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(TMV3662)

Machine Id
934066

Component
Natural Gas Engine

Fluid
PETRO CANADA DURON GEO LD 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Sample)

Wear

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| SAMPLE INFORMATION | | method | limit/base | current | history1 | history2 |
|--------------------|-------------|-------------|------------|--------------------|-------------|-------------|
| Sample Number | Client Info | | | GFL0125245 | GFL0114401 | GFL0103947 |
| Sample Date | Client Info | | | 21 Jun 2024 | 18 Mar 2024 | 28 Dec 2023 |
| Machine Age | hrs | Client Info | | 2034 | 15655 | 7686 |
| Oil Age | hrs | Client Info | | 0 | 0 | 7686 |
| Oil Changed | Client Info | | | Not Changed | Changed | Changed |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |

| CONTAMINATION | | method | limit/base | current | history1 | history2 |
|---------------|-----------|--------|------------|------------|----------|----------|
| Water | WC Method | | >0.1 | NEG | NEG | NEG |

| WEAR METALS | | method | limit/base | current | history1 | history2 |
|-------------|-----|-------------|------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m | >50 | 23 | 22 | 31 |
| Chromium | ppm | ASTM D5185m | >4 | 3 | 2 | <1 |
| Nickel | ppm | ASTM D5185m | >2 | 1 | 1 | 0 |
| Titanium | ppm | ASTM D5185m | | <1 | <1 | 0 |
| Silver | ppm | ASTM D5185m | >3 | <1 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >9 | 38 | 31 | 20 |
| Lead | ppm | ASTM D5185m | >30 | 1 | 2 | <1 |
| Copper | ppm | ASTM D5185m | >35 | 4 | 6 | 17 |
| Tin | ppm | ASTM D5185m | >4 | <1 | 2 | <1 |
| Vanadium | ppm | ASTM D5185m | | <1 | <1 | 0 |
| Cadmium | ppm | ASTM D5185m | | <1 | <1 | 0 |

| ADDITIVES | | method | limit/base | current | history1 | history2 |
|------------|-----|-------------|------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m | 50 | 8 | 11 | 14 |
| Barium | ppm | ASTM D5185m | 5 | <1 | 2 | 2 |
| Molybdenum | ppm | ASTM D5185m | 50 | 63 | 66 | 61 |
| Manganese | ppm | ASTM D5185m | 0 | 1 | 3 | 15 |
| Magnesium | ppm | ASTM D5185m | 560 | 669 | 632 | 762 |
| Calcium | ppm | ASTM D5185m | 1510 | 1869 | 1858 | 1387 |
| Phosphorus | ppm | ASTM D5185m | 780 | 915 | 791 | 698 |
| Zinc | ppm | ASTM D5185m | 870 | 1127 | 1071 | 924 |
| Sulfur | ppm | ASTM D5185m | 2040 | 2752 | 2816 | 2354 |





| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
|--------------|-----|-------------|------------|------------|----------|----------|
| Silicon | ppm | ASTM D5185m | >+100 | 8 | 8 | 24 |
| Sodium | ppm | ASTM D5185m | | 8 | 6 | 4 |
| Potassium | ppm | ASTM D5185m | >20 | 129 | 112 | 66 |

| INFRA-RED | | method | limit/base | current | history1 | history2 |
|-----------|----------|-------------|------------|-------------|----------|----------|
| Soot % | % | *ASTM D7844 | | 0 | 0 | 0 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 11.1 | 11.2 | 11.2 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 24.7 | 23.3 | 21.8 |

| FLUID DEGRADATION | | method | limit/base | current | history1 | history2 |
|-------------------|----------|-------------|------------|-------------|----------|----------|
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 19.9 | 19.8 | 19.6 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 10.2 | 4.6 | 3.6 | 5.0 |







OIL ANALYSIS REPORT



| PARAMETER | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 100°C | cSt | ASTM D445 | 15.1 | 14.7 | 14.6 |

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0125245
Lab Number : 06224230
Unique Number : 11102427
Test Package : FLEET

Received : 28 Jun 2024
Tested : 01 Jul 2024
Diagnosed : 01 Jul 2024 - Angela Borella

GFL Environmental - 865 - East Mount Hauling
 7213 East Mount Houston Road
 Houston, TX
 US 77050
 Contact: TECHNICIAN ACCOUNT
 wcgfldemo@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: