


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**(89654X) Walgreens - Tractor**  
 Machine Id  
**[Walgreens - Tractor] 136A69075**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0128631</b>	PCA0112840	PCA0103793
Sample Date	Client Info	<b>26 Jun 2024</b>	21 Feb 2024	13 Oct 2023
Machine Age	mls Client Info	<b>690598</b>	668367	650839
Oil Age	mls Client Info	<b>22231</b>	51032	33504
Oil Changed	Client Info	<b>Not Changed</b>	Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	<b>11</b>	25	21
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	1	1
Nickel	ppm ASTM D5185m >2	<b>1</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m >3	<b>&lt;1</b>	0	0
Aluminum	ppm ASTM D5185m >30	<b>7</b>	17	12
Lead	ppm ASTM D5185m >30	<b>&lt;1</b>	1	0
Copper	ppm ASTM D5185m >150	<b>2</b>	6	5
Tin	ppm ASTM D5185m >5	<b>1</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	<1	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	<b>4</b>	0	0
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 50	<b>59</b>	65	64
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 950	<b>1008</b>	1052	1018
Calcium	ppm ASTM D5185m 1050	<b>1103</b>	1189	1126
Phosphorus	ppm ASTM D5185m 995	<b>1115</b>	1076	1085
Zinc	ppm ASTM D5185m 1180	<b>1388</b>	1376	1361
Sulfur	ppm ASTM D5185m 2600	<b>3849</b>	2734	3032

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>3</b>	4	4
Sodium	ppm ASTM D5185m	<b>1</b>	3	2
Potassium	ppm ASTM D5185m >20	<b>9</b>	21	15




## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.5</b>	0.8	0.6
Nitration	Abs/cm *ASTM D7624 >20	<b>8.1</b>	10.4	9.1
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.7</b>	23.8	21.4

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.4</b>	19.9	17.9
Base Number (BN)	mg KOH/g ASTM D2896	<b>7.9</b>	5.3	6.9





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.6	11.8

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0128631  
**Lab Number** : **06225457**  
**Unique Number** : 11103654  
**Test Package** : FLEET  
**Received** : 01 Jul 2024  
**Tested** : 02 Jul 2024  
**Diagnosed** : 02 Jul 2024 - Wes Davis

**Transervice - Shop 1364 - Berkeley-Mt. Vernon**  
 5100 Lake Terrace NE  
 Mt. Vernon, IL  
 US 62864  
 Contact: Erien White  
 ewhite@transervice.com  
 T: (618)244-8726  
 F: (618)244-8791

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)