



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area

MONTGOMERY

Machine Id


MACK 925034-152592

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (--- LTR)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0127771	GFL0088022	GFL0118433
Sample Date	Client Info	28 Jun 2024	23 May 2024	06 May 2024
Machine Age	hrs	24748	24498	24361
Oil Age	hrs	24748	24498	24361
Oil Changed	Client Info	N/A	Not Changd	N/A
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >120	4	6	5
Chromium	ppm ASTM D5185m >20	<1	<1	<1
Nickel	ppm ASTM D5185m >5	<1	<1	<1
Titanium	ppm ASTM D5185m >2	<1	<1	<1
Silver	ppm ASTM D5185m >2	<1	1	0
Aluminum	ppm ASTM D5185m >20	3	3	2
Lead	ppm ASTM D5185m >40	<1	1	1
Copper	ppm ASTM D5185m >330	<1	2	1
Tin	ppm ASTM D5185m >15	<1	1	1
Vanadium	ppm ASTM D5185m	<1	<1	<1
Cadmium	ppm ASTM D5185m	<1	<1	<1

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<1	<1	<1
Barium	ppm ASTM D5185m 0	<1	<1	0
Molybdenum	ppm ASTM D5185m 60	63	60	54
Manganese	ppm ASTM D5185m 0	<1	<1	<1
Magnesium	ppm ASTM D5185m 1010	902	963	883
Calcium	ppm ASTM D5185m 1070	1045	1082	1007
Phosphorus	ppm ASTM D5185m 1150	946	1038	970
Zinc	ppm ASTM D5185m 1270	1151	1250	1166
Sulfur	ppm ASTM D5185m 2060	2602	3292	3260

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	4	6	5
Sodium	ppm ASTM D5185m	2	6	2
Potassium	ppm ASTM D5185m >20	2	3	3

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >4	0.1	0.2	0.2
Nitration	Abs/cm *ASTM D7624 >20	5.5	7.5	6.7
Sulfation	Abs/.1mm *ASTM D7415 >30	17.7	18.1	18.2


FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	13.5	14.8	14.4
Base Number (BN)	mg KOH/g ASTM D2896 9.8	8.5	8.0	8.5




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C



VISUAL


	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES


	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.8	13.5

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0127771
 Lab Number : 06226010
 Unique Number : 11109503
 Test Package : FLEET

Received : 02 Jul 2024
 Tested : 03 Jul 2024
 Diagnosed : 03 Jul 2024 - Wes Davis

GFL Environmental - 955 - Montgomery
 1121 Wilbanks St
 Montgomery, AL
 US 36108
 Contact: LISA REEVES

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: