

OIL ANALYSIS REPORT

Area WILLMAR Machine Id Unit 01 DB040101E

Natural Gas Engine Fluid DIESEL ENGINE OIL SAE 40 (250 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. (Customer Sample Comment: 30 Gallons Make-up Oil)

Wear


All component wear rates are normal.

Contamination

Fuel content negligible. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0105952	PCA0105951	PCA0105950
Sample Date		Client Info		28 Jun 2024	30 May 2024	26 Apr 2024
Machine Age	hrs	Client Info		6732	6530	6283
Oil Age	hrs	Client Info		6732	6530	6283
Oil Changed		Client Info		Filtered	Filtered	Filtered
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	2	6	3
Chromium	ppm	ASTM D5185m	>4	0	<1	0
Nickel	ppm	ASTM D5185m	>2	0	<1	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>9	1	2	0
Lead	ppm	ASTM D5185m	>30	<1	3	<1
Copper	ppm	ASTM D5185m	>35	<1	3	5
Tin	ppm	ASTM D5185m	>4	<1	1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		<1	<1	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	<1	0	0
Barium	ppm	ASTM D5185m	10	0	0	<1
Molybdenum	ppm	ASTM D5185m	100	3	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m	450	935	917	897
Calcium	ppm	ASTM D5185m	3000	1089	1101	1073
Phosphorus	ppm	ASTM D5185m	1150	1192	1030	1164
Zinc	ppm	ASTM D5185m	1350	1367	1348	1315
Sulfur	ppm	ASTM D5185m	4250	3681	3350	3469
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+100	2	2	2
Sodium	ppm	ASTM D5185m	>216	3	2	2
Potassium	ppm	ASTM D5185m	>20	3	4	0
Fuel	%	ASTM D3524	>4.0	1.6	1.4	1.1
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	4.2	4.1	4.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	13.1	13.1	13.0
FLUID DEGRA		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	6.9	6.9	6.9
Acid Number (AN)	mg KOH/g	ASTM D8045		1.50	1.45	1.55
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	8.75	8.66	8.50


Sample Rating Trend





OIL ANALYSIS REPORT













To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: MAGWIL [WUSCAR] 06226812 (Generated: 07/05/2024 13:10:34) Rev: 1

Certificate 12367

Submitted By: Andrew Lauer

andrew.lauer@magellanlp.com

n79/74 26/24

Page 2 of 2

E:

Willmar, MN

T: (320)808-4364

US 56201

NONE

NONE

NONE

NONE

NONE

NONE

NORML

NORML

NEG

NEG

13.6