


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Area  
**Walgreens - Tractor**  
 Machine #  
**[Walgreens - Tractor] 136A63373**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0127887</b>	PCA0117899	PCA0105454
Sample Date	Client Info			<b>21 Jun 2024</b>	28 Mar 2024	27 Dec 2023
Machine Age	mls	Client Info		<b>95058</b>	80762	70596
Oil Age	mls	Client Info		<b>25000</b>	35166	29573
Oil Changed	Client Info			<b>Not Changed</b>	Changed	Not Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>2.0		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>13</b>	24	20
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>4</b>	2	6
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>&lt;1</b>	<1	0
Aluminum	ppm	ASTM D5185m	>20	<b>5</b>	6	5
Lead	ppm	ASTM D5185m	>40	<b>1</b>	6	4
Copper	ppm	ASTM D5185m	>330	<b>5</b>	6	12
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	2	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>11</b>	11	15
Barium	ppm	ASTM D5185m	0	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m	50	<b>56</b>	64	59
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	2	<1
Magnesium	ppm	ASTM D5185m	950	<b>919</b>	908	854
Calcium	ppm	ASTM D5185m	1050	<b>1179</b>	1248	1256
Phosphorus	ppm	ASTM D5185m	995	<b>1105</b>	1052	986
Zinc	ppm	ASTM D5185m	1180	<b>1307</b>	1338	1359
Sulfur	ppm	ASTM D5185m	2600	<b>3592</b>	3434	3037

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>6</b>	13	12
Sodium	ppm	ASTM D5185m		<b>2</b>	2	2
Potassium	ppm	ASTM D5185m	>20	<b>11</b>	18	16

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.2</b>	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.5</b>	9.4	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.8</b>	22.6	21.3

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.7</b>	19.9	18.8
Base Number (BN)	mg KOH/g	ASTM D2896		<b>7.9</b>	5.6	7.1





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.1	11.3

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0127887      **Received** : 02 Jul 2024  
**Lab Number** : 06226881      **Tested** : 05 Jul 2024  
**Unique Number** : 11110374      **Diagnosed** : 05 Jul 2024 - Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1366 - Berkeley-Woodland**  
 2370 East Main Street  
 Woodland, CA  
 US 95776  
 Contact: Gary Mann  
 gmann@transervice.com  
 T: (530)666-7771  
 F: (530)406-7971

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)