


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Area  
**(AU767S) Supermarket - Tractor**  
 Machine Id  
**FREIGHTLINER 107A8826**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (11 GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0124127</b>	PCA0116971	PCA0104064
Sample Date	Client Info			<b>18 Jun 2024</b>	03 Feb 2024	04 Oct 2023
Machine Age	mls Client Info			<b>189209</b>	189209	178076
Oil Age	mls Client Info			<b>18875</b>	11133	13161
Oil Changed	Client Info			<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	<b>10</b>	9	12
Chromium	ppm	ASTM D5185m	>5	<b>1</b>	<1	1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>30	<b>7</b>	4	9
Lead	ppm	ASTM D5185m	>30	<b>0</b>	0	0
Copper	ppm	ASTM D5185m	>150	<b>2</b>	4	5
Tin	ppm	ASTM D5185m	>5	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>5</b>	9	7
Barium	ppm	ASTM D5185m	0	<b>0</b>	8	0
Molybdenum	ppm	ASTM D5185m	50	<b>65</b>	64	63
Manganese	ppm	ASTM D5185m	0	<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185m	950	<b>936</b>	851	885
Calcium	ppm	ASTM D5185m	1050	<b>1075</b>	1022	1052
Phosphorus	ppm	ASTM D5185m	995	<b>999</b>	893	1018
Zinc	ppm	ASTM D5185m	1180	<b>1218</b>	1127	1225
Sulfur	ppm	ASTM D5185m	2600	<b>2706</b>	2869	2754

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<b>4</b>	3	5
Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	0	3
Potassium	ppm	ASTM D5185m	>20	<b>4</b>	5	10

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.6</b>	0.5	0.8
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.7</b>	6.9	8.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.2</b>	18.7	20.3

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.4</b>	14.0	15.5
Base Number (BN)	mg KOH/g	ASTM D2896		<b>8.5</b>	8.5	7.2





# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.4</b>	11.5	11.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0124127      **Received** : 03 Jul 2024  
**Lab Number** : **06227044**      **Tested** : 05 Jul 2024  
**Unique Number** : 11110537      **Diagnosed** : 05 Jul 2024 - Wes Davis  
**Test Package** : FLEET

**Transervice - Shop 1071 - Supermarket-Dayton**  
 60 A Tower Road  
 Dayton, NJ  
 US 08810  
 Contact: Brian Quinn  
 bquinn@transervice.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: