

OIL ANALYSIS REPORT

Sample Rating Trend

PETRO CANADA DURON SHP 15W40 (11 GAL)

DIAGNOSIS

Diesel Engine

(EPI996)

10700

Recommendation

We recommend that you drain the oil from the component if this has not already been done. We recommend an early resample to monitor this condition.

Wear

Area

All component wear rates are normal.

Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.


SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0077448	GFL0111497	GFL0068820
Sample Date		Client Info		26 Jun 2024	26 Apr 2024	13 Mar 2024
Machine Age	hrs	Client Info		2097	1947	1709
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				ABNORMAL	NORMAL	ABNORMAL
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS	5	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>75	28	46	55
Chromium	ppm	ASTM D5185m	>5	2	4	7
Nickel	ppm	ASTM D5185m	>4	<1	0	0
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	8	8	0 10
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>100	1	<1	3
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	6	5	6
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	52	59	56
Manganese	ppm	ASTM D5185m	0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1010	917	931	924
Calcium						
Phosphorus	ppm	ASTM D5185m	1070	976	1020	1010
1.1000010100		ASTM D5185m ASTM D5185m	1070 1150	976 986	1020 1009	
•	ppm					1010
•	ppm ppm	ASTM D5185m	1150	986	1009	1010 1011
Zinc	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	1150 1270	986 1177	1009 1215	1010 1011 1193
Zinc Sulfur CONTAMINAN	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	1150 1270 2060 limit/base	986 1177 3331	1009 1215 3315	1010 1011 1193 3037
Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm TS	ASTM D5185m ASTM D5185m ASTM D5185m method	1150 1270 2060 limit/base	986 1177 3331 current	1009 1215 3315 history1	1010 1011 1193 3037 history2
Zinc Sulfur CONTAMINAN Silicon	ppm ppm ppm ppm TS ppm	ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D5185m	1150 1270 2060 limit/base	986 1177 3331 current 10	1009 1215 3315 history1 18	1010 1011 1193 3037 history2 ▲ 27
Zinc Sulfur CONTAMINAN Silicon Sodium	ppm ppm ppm ppm TS ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	1150 1270 2060 limit/base >25	986 1177 3331 current 10 6	1009 1215 3315 history1 18 6	1010 1011 1193 3037 history2 ▲ 27 6
Zinc Sulfur CONTAMINAN Silicon Sodium Potassium	ppm ppm ppm ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	1150 1270 2060 limit/base >25 >20	986 1177 3331 current 10 6 2	1009 1215 3315 history1 18 6 <1	1010 1011 1193 3037 history2 ▲ 27 6 <1
Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel	ppm ppm ppm ppm TS ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	1150 1270 2060 limit/base >25 >20 >3.0	986 1177 3331 current 10 6 2 2 ► 5.2	1009 1215 3315 history1 18 6 <1 <1.0	1010 1011 1193 3037 history2 ▲ 27 6 <1 <1.0
Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot %	ppm ppm ppm ppm TS ppm ppm %	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524	1150 1270 2060 limit/base >25 >20 >3.0 limit/base	986 1177 3331 current 10 6 2 2 ▲ 5.2 current	1009 1215 3315 history1 18 6 <1 <1.0 history1	1010 1011 1193 3037 history2 ▲ 27 6 <1 <1.0 history2
Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration	ppm ppm ppm ppm TS ppm ppm %	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524	1150 1270 2060 imit/base >25 >20 >3.0 imit/base >6	986 1177 3331 <u>current</u> 10 6 2 2 5.2 <u>current</u> 0.6	1009 1215 3315 history1 18 6 <1 <1.0 history1 0.5	1010 1011 1193 3037 history2 ▲ 27 6 <1 <1.0 history2 0.5
Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm % % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D3524 method *ASTM D7844	1150 1270 2060 limit/base >25 >20 >3.0 limit/base >6 >20	986 1177 3331 <u>current</u> 10 6 2 2 ▲ 5.2 <u>current</u> 0.6 7.7	1009 1215 3315 history1 18 6 <1 <1.0 +istory1 0.5 7.8	1010 1011 1193 3037 history2 ▲ 27 6 <1 <1.0 history2 0.5 7.2
Zinc Sulfur CONTAMINAN Silicon Sodium Potassium Fuel INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm % % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7844 *ASTM D7844 *ASTM D7844	1150 1270 2060 >25 >20 >3.0 limit/base >6 >20 >30	986 1177 3331 <u>current</u> 10 6 2 2 5.2 <u>current</u> 0.6 7.7 18.6	1009 1215 3315 history1 18 6 <1 <1.0 history1 0.5 7.8 19.9	1010 1011 1193 3037 history2 ▲ 27 6 <1 <1.0 history2 0.5 7.2 19.1



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<mark>/</mark> 12.4	13.8	13.6
GRAPHS						

Ferrous Alloys







Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 GFL Environmental - 072 - Americus - Transwaste : GFL0077448 Sample No. Received : 05 Jul 2024 361 McMath Mill Road Lab Number : 06228278 Tested : 09 Jul 2024 Americus, GA Unique Number : 11111771 Diagnosed : 09 Jul 2024 - Wes Davis US 31719 Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel) Contact: RICHARD HEINZERLING Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369. richard.heinzerling@gflenv.com * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (229)924-3669 E:

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: GFL072 [WUSCAR] 06228278 (Generated: 07/09/2024 09:38:19) Rev: 1

Submitted By: George Sawyer Page 2 of 2