




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(EIB893)

Machine Id

3641

Component

Diesel Engine

Fluid

PETRO CANADA DURON SHP 15W40 (8 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0077470	GFL0089586	GFL0089600
Sample Date	Client Info		26 Jun 2024	20 Mar 2024	27 Feb 2024
Machine Age	hrs	Client Info	1484	0	0
Oil Age	hrs	Client Info	0	0	0
Oil Changed	Client Info		Not Changed	Not Changd	Not Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >75	16	52	111
Chromium	ppm	ASTM D5185m >5	<1	5	2
Nickel	ppm	ASTM D5185m >4	<1	1	4
Titanium	ppm	ASTM D5185m >2	<1	2	<1
Silver	ppm	ASTM D5185m >2	<1	0	0
Aluminum	ppm	ASTM D5185m >15	7	41	8
Lead	ppm	ASTM D5185m >25	0	1	3
Copper	ppm	ASTM D5185m >100	0	9	5
Tin	ppm	ASTM D5185m >4	<1	1	<1
Vanadium	ppm	ASTM D5185m	0	<1	<1
Cadmium	ppm	ASTM D5185m	0	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	2	2	8
Barium	ppm	ASTM D5185m 0	0	<1	0
Molybdenum	ppm	ASTM D5185m 60	51	62	94
Manganese	ppm	ASTM D5185m 0	<1	1	<1
Magnesium	ppm	ASTM D5185m 1010	917	905	1109
Calcium	ppm	ASTM D5185m 1070	946	1103	1343
Phosphorus	ppm	ASTM D5185m 1150	985	1072	1188
Zinc	ppm	ASTM D5185m 1270	1192	1205	1385
Sulfur	ppm	ASTM D5185m 2060	3363	2628	2760

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	12	23	11
Sodium	ppm	ASTM D5185m	4	4	10
Potassium	ppm	ASTM D5185m >20	3	23	6

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	0.7	0.9	1
Nitration	Abs/cm	*ASTM D7624 >20	7.0	11.0	13.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	18.0	22.7	27.5


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	12.8	18.9	28.4
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	8.2	5.8	6.5




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C



VISUAL


	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES


	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	12.9	13.3

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0077470
 Lab Number : 06228282
 Unique Number : 11111775
 Test Package : FLEET

Received : 05 Jul 2024
 Tested : 05 Jul 2024
 Diagnosed : 05 Jul 2024 - Wes Davis

GFL Environmental - 072 - Americus - Transwaste
 361 McMath Mill Road
 Americus, GA
 US 31719

Contact: RICHARD HEINZERLING
 richard.heinzerling@gflenv.com
 T: (229)924-3669

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: