




# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id

**425118**

Component

**Diesel Engine**

Fluid

**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0119882</b>	GFL0097855	GFL0085300
Sample Date	Client Info		<b>01 Jul 2024</b>	25 Mar 2024	09 Oct 2023
Machine Age	hrs	Client Info	<b>0</b>	0	0
Oil Age	hrs	Client Info	<b>500</b>	490	600
Oil Changed	Client Info		<b>N/A</b>	N/A	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	<b>45</b>	42	21
Chromium	ppm	ASTM D5185m >4	<b>2</b>	2	1
Nickel	ppm	ASTM D5185m >2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >25	<b>1</b>	2	1
Lead	ppm	ASTM D5185m >45	<b>11</b>	11	<1
Copper	ppm	ASTM D5185m >85	<b>13</b>	12	5
Tin	ppm	ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>10</b>	9	25
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	12
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	53	50
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 1010	<b>998</b>	928	800
Calcium	ppm	ASTM D5185m 1070	<b>1350</b>	1269	1327
Phosphorus	ppm	ASTM D5185m 1150	<b>1079</b>	894	906
Zinc	ppm	ASTM D5185m 1270	<b>1347</b>	1218	1119
Sulfur	ppm	ASTM D5185m 2060	<b>3383</b>	3148	2798

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	<b>8</b>	8	11
Sodium	ppm	ASTM D5185m	<b>7</b>	6	10
Potassium	ppm	ASTM D5185m >20	<b>&lt;1</b>	0	3

## INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.4</b>	0.5	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>11.4</b>	11.9	9.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>26.0</b>	26.9	23.3

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>26.0</b>	28.4	22.8
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>7.0</b>	5.7	7.7







# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.9</b>	12.9	14.2

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0119882      **Received** : 05 Jul 2024  
**Lab Number** : 06229459      **Tested** : 09 Jul 2024  
**Unique Number** : 11112952      **Diagnosed** : 09 Jul 2024 - Sean Felton  
**Test Package** : FLEET

**GFL Environmental - 958 - Tri County HC Morton**  
 1090 W. Jefferson St.  
 Morton, IL  
 US 61550  
 Contact: Bryan Link  
 blink@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)